

236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 14  
Dated 18/09/2015  
Printed on 25/07/2017  
Page n. 1/14

**10279-10280 - 1940 BUMPER FLEX**

## Safety data sheet

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: 10279-10280  
Product name 1940 BUMPER FLEX

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Polyester putty

#### 1.3. Details of the supplier of the safety data sheet

Name GELSON SRL  
Full address Via Varese 11/13  
District and Country 20020 Lainate (MI)  
Italia  
Tel. +39 02 9370640  
Fax +39 02 93797341

e-mail address of the competent person  
responsible for the Safety Data Sheet info@gelson.it

Australian distributor OZ-GEL  
236 Maddington Rd  
Maddington 6109 Western Australia  
ozgel@iinet.net.au

Australian distributor phone number  
Local Distributor 0418 913 426 (general information)

#### 1.4. Emergency telephone number

For urgent inquiries refer to  
POISONS INFORMATION CENTRE  
Australia Tel. 13 11 26  
New Zealand Tel. 0800 764 766

### SECTION 2. Hazards identification.

#### 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Reproductive toxicity, category 2	H361d	Suspected of damaging the unborn child.
Specific target organ toxicity - repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.

#### 2.2. Label elements.

236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 14  
Dated 18/09/2015  
Printed on 25/07/2017  
Page n. 2/14

## 10279-10280 - 1940 BUMPER FLEX

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

**H226** Flammable liquid and vapour.  
**H361d** Suspected of damaging the unborn child.  
**H372** Causes damage to organs through prolonged or repeated exposure.  
**H319** Causes serious eye irritation.  
**H315** Causes skin irritation.

Precautionary statements:

**P201** Obtain special instructions before use.  
**P210** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
**P233** Keep container tightly closed.  
**P280** Wear protective gloves / clothing and eye / face protection.  
**P303+P361+P353** IF ON SKIN (or hair): take off immediately all contaminated clothing. Rinse skin with water / shower.  
**P308+P313** IF exposed or concerned: Get medical advice / attention.

**Contains:** STYRENE

### 2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

## SECTION 3. Composition/information on ingredients.

### 3.1. Substances.

Information not relevant.

### 3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification 1272/2008 (CLP).
<b>STYRENE</b>		
CAS. 100-42-5	10 - 30	Flam. Liq. 3 H226, Repr. 2 H361d, Acute Tox. 4 H332, STOT RE 1 H372, Eye Irrit. 2 H319, Skin Irrit. 2 H315, Note D
EC. 202-851-5		
INDEX. 601-026-00-0		

**236 Maddington Road Maddington 6109**  
**Western Australia**  
**Ph: 08 9493 7948 Fax: 08 9493 2414**  
**Email: ozgel@iinet.net.au**  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 14  
Dated 18/09/2015  
Printed on 25/07/2017  
Page n. 3/14

## 10279-10280 - 1940 BUMPER FLEX

Reg. no. 01-2119457861-32

### **N-ethyl-2-pyrrolidone;**

CAS. 2687-91-4

0 - 0,3

Repr. 1B H360D, Eye Dam. 1  
H318

EC. 220-250-6

INDEX. 616-208-00-5

Reg. no. 01-2119472138

### **DIISOPROPANOL-p-TOLUIDINA**

CAS. 38668-48-3

0 - 0,25005

Acute Tox. 2 H300, Eye Irrit.  
2 H319, Aquatic Chronic 3  
H412

EC. 254-075-1

INDEX. -

Reg. no. 01-2119980937-17

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## SECTION 4. First aid measures.

### 4.1. Description of first aid measures.

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

**INHALATION:** Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

**INGESTION:** Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

### 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

## SECTION 5. Firefighting measures.

### 5.1. Extinguishing media.

#### SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

#### UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 14  
Dated 18/09/2015  
Printed on 25/07/2017  
Page n. 4/14

## 10279-10280 - 1940 BUMPER FLEX

### 5.2. Special hazards arising from the substance or mixture.

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

### 5.3. Advice for firefighters.

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal firefighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures.

### 6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and Storage

### 7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground

**236 Maddington Road Maddington 6109**  
**Western Australia**  
**Ph: 08 9493 7948 Fax: 08 9493 2414**  
**Email: ozgel@iinet.net.au**  
 A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
 ABN: 38 926 088 116



Revision nr. 14  
 Dated 18/09/2015  
 Printed on 25/07/2017  
 Page n. 5/14

## 10279-10280 - 1940 BUMPER FLEX

level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s).

Information not available.

## SECTION 8. Exposure controls/personal protection.

### 8.1. Control parameters.

Regulatory References:

BEL	Belgique	AR du 11/3/2002. La liste est mise à jour pour 2010
DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GRB	United Kingdom	EH40/2005 Workplace exposure limits
IRL	Éire	Code of Practice Chemical Agent Regulations 2011
NLD	Nederland	Databank of the social and Economic Concil of Netherlands (SER) Values, AF 2011:18
	TLV-ACGIH	ACGIH 2014

### STYRENE

#### Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
VLEP	BEL	216	50	432	100	SKIN.
AGW	DEU	86	20	172	40	
MAK	DEU	86	20	172	40	
VLA	ESP	86	20	172	40	
VLEP	FRA	215	50			
WEL	GRB	430	100	1080	250	
OEL	IRL	85	20	170	40	
OEL	NLD	107				
TLV-ACGIH		85	20	170	40	

### DIISOPROPANOL-p-TOLUIDINA

Predicted no-effect concentration - PNEC.

Normal value in fresh water 0,017 mg/l

**236 Maddington Road Maddington 6109**  
**Western Australia**  
**Ph: 08 9493 7948 Fax: 08 9493 2414**  
**Email: ozgel@iinet.net.au**  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 14  
Dated 18/09/2015  
Printed on 25/07/2017  
Page n. 6/14

## 10279-10280 - 1940 BUMPER FLEX

Normal value in marine water 0,00782 mg/l  
Normal value of STP microorganisms 199,5 mg/l

### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers.			Effects on workers			Chronic local	Chronic systemic
	Acute local	Acute systemic	Chronic local	Acute local	Acute systemic	Chronic local		
Inhalation.							VND	2 mg/m <sup>3</sup>
Skin.							VND	0,6 mg/kg bw/d

### N-ethyl-2-pyrrolidone;

Predicted no-effect concentration - PNEC.

Normal value in fresh water 0,25 mg/l  
Normal value in marine water 0,025 mg/l  
Normal value for fresh water sediment 1,91 mg/kg  
Normal value for marine water sediment 0,191 mg/kg  
Normal value for the terrestrial compartment 0,235 mg/kg

### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers.			Effects on workers			Chronic local	Chronic systemic
	Acute local	Acute systemic	Chronic local	Acute local	Acute systemic	Chronic local		
Inhalation.			VND		10 mg/m <sup>3</sup>		VND	40 mg/m <sup>3</sup>
Skin.			VND		4 mg/kg bw/d		VND	8 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

## 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

### SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

**236 Maddington Road Maddington 6109**  
**Western Australia**  
**Ph: 08 9493 7948 Fax: 08 9493 2414**  
**Email: ozgel@iinet.net.au**  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 14  
Dated 18/09/2015  
Printed on 25/07/2017  
Page n. 7/14

## 10279-10280 - 1940 BUMPER FLEX

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

### ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9. Physical and chemical properties.

### 9.1. Information on basic physical and chemical properties.

Appearance	pasty
Colour	black
Odour	characteristic of solvent
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	29 °C.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	1,730 Kg/l
Solubility	insoluble in water
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

### 9.2. Other information.

VOC (Directive 2004/42/EC) :	16,09 %	-	278,36	g/litre.
VOC (volatile carbon) :	14,75 %	-	255,23	g/litre.

## SECTION 10. Stability and reactivity.

### 10.1. Reactivity.

**236 Maddington Road Maddington 6109**  
**Western Australia**  
**Ph: 08 9493 7948 Fax: 08 9493 2414**  
**Email: ozgel@iinet.net.au**  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 14  
Dated 18/09/2015  
Printed on 25/07/2017  
Page n. 8/14

## **10279-10280 - 1940 BUMPER FLEX**

There are no particular risks of reaction with other substances in normal conditions of use.

STYRENE: polymerises readily above 65°C/149°F with risk of fire and explosion; added with an inhibitor that requires a small amount of dissolved oxygen at temperatures < 25°C/77°F.

### **10.2. Chemical stability.**

The product is stable in normal conditions of use and storage.

### **10.3. Possibility of hazardous reactions.**

The vapours may also form explosive mixtures with the air.

STYRENE: can react dangerously with peroxides and strong acids. May polymerise on contact with: aluminium trichloride, azobisisobutyronitrile, dibenzoyl peroxide, sodium. Risk of explosion on contact with: butyllithium, chlorosulphuric acid, di-tert-butyl peroxide, oxidising agents, oxygen.

### **10.4. Conditions to avoid.**

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

### **10.5. Incompatible materials.**

STYRENE: avoid oxidising agents, copper and strong acids; it dissolves various types of plastic materials, but not polychloroprene and polyvinyl alcohol.

### **10.6. Hazardous decomposition products.**

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

## **SECTION 11. Toxicological information.**

### **11.1. Information on toxicological effects.**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product must be handled carefully because of its possible teratogenic effects, which may be toxic and damage the foetus development.

This product may cause functional disorders or morphological mutations after repeated or prolonged exposure and/or may accumulate inside the human body and is thus graded as dangerous.

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation. Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin. Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

STYRENE: Acute toxicity following inhalation at 1000 ppm involves the central nervous system with headache and dizziness, lack of coordination; irritation of the mucous membranes of the eyes and respiratory tract occurs at 500 ppm concentrations. Chronic exposure produces depression of the Central and peripheral nervous system with loss of memory, headache and somnolence starting at 20 ppm; digestive disorders with nausea and loss of appetite; irritation of the respiratory tract with chronic bronchitis and dermatosis.



236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 14  
Dated 18/09/2015  
Printed on 25/07/2017  
Page n. 9/14

## 10279-10280 - 1940 BUMPER FLEX

N-ethyl-2-pyrrolidone;  
LD50 (Oral).3200 mg/kg  
LD50 (Dermal).> 2000 mg/kg  
LC50 (Inhalation).> 5,1 mg/l/4h

STYRENE  
LD50 (Oral).5000 mg/kg Rat  
LC50 (Inhalation).11,8 mg/l/4h Rat

DIISOPROPANOL-p-TOLUIDINA  
LD50 (Oral).> 2000 mg/kg  
LD50 (Dermal).25 mg/kg

### SECTION 12. Ecological information.

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

#### 12.1. Toxicity.

N-ethyl-2-pyrrolidone;  
LC50 - for Fish. > 464 mg/l/96h  
EC50 - for Crustacea. > 104 mg/l/48h  
EC50 - for Algae / Aquatic  
Plants. 101 mg/l/72h

#### 12.2. Persistence and degradability.

STYRENE  
Solubility in water. 320 mg/l

Rapidly biodegradable.

#### 12.3. Bioaccumulative potential.

STYRENE  
Partition coefficient: n-  
octanol/water. 2,96  
BCF. 74

#### 12.4. Mobility in soil.

STYRENE  
Partition coefficient:  
soil/water. 2,55

#### 12.5. Results of PBT and vPvB assessment.

236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 14  
Dated 18/09/2015  
Printed on 25/07/2017  
Page n. 10/14

## 10279-10280 - 1940 BUMPER FLEX

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### 12.6. Other adverse effects.

Information not available.

## SECTION 13. Disposal considerations.

### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information.

### 14.1. UN number.

WHEN SHIPPED WITHOUT HARDENER:

ADR / RID, IMDG, IATA: 1263

The product, if packaged in packages of less than 450 litres, is not subject to ADR regulations as stated in 2.2.3.1.5.

The product, if packaged in packages of less than 30 litres, is not subject to obligations relating to marking, labelling and package testing in accordance with 2.3.2.5 of the IMDG CODE.

WHEN SHIPPED WITH HARDENER:

ADR / RID, IMDG, IATA: 3269

### 14.2. UN proper shipping name.

ADR / RID: POLYESTER  
RESIN KIT  
IMDG: POLYESTER  
RESIN KIT  
(BENZOYL  
PEROXIDE)  
IATA: POLYESTER  
RESIN KIT

### 14.3. Transport hazard class(es).

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 14  
Dated 18/09/2015  
Printed on 25/07/2017  
Page n. 11/14

## 10279-10280 - 1940 BUMPER FLEX

### 14.4. Packing group.

ADR / RID, IMDG, III  
IATA:

### 14.5. Environmental hazards.

ADR / RID: Environmentally  
Hazardous.



IMDG: Marine Pollutant.



IATA: NO

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

### 14.6. Special precautions for user.

ADR / RID:	HIN - Kemler: --	Limited Quantities: 5 L	Tunnel restriction code: (E)
IMDG:	Special Provision: - EMS: F-E, S-D	Limited Quantities: 5 L	
IATA:	Cargo: Pass.:	Maximum quantity: 10 Kg Maximum quantity: 10 Kg	Packaging instructions: 370 Packaging instructions: 370
	Special Instructions:	A66, A163	

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

## SECTION 15. Regulatory information.

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category. 6

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.  
Point. 3 - 40

#### Contained substance.

Point. 30 N-ethyl-2-pyrrolidone;  
Reg. no.: 01-  
2119472138

Substances in Candidate List (Art. 59 REACH).

236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 14  
Dated 18/09/2015  
Printed on 25/07/2017  
Page n. 12/14

## 10279-10280 - 1940 BUMPER FLEX

None.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) :

Bodyfiller/stopper.

VOC given in g/litre of product in a ready-to-use condition :

Limit value: 250,00

VOC of product : 70,00

- Catalysed with : 2,00 %

INDURITORE IN  
PASTA

### 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

## SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 3</b>	Flammable liquid, category 3
<b>Repr. 1B</b>	Reproductive toxicity, category 1B
<b>Repr. 2</b>	Reproductive toxicity, category 2
<b>Acute Tox. 2</b>	Acute toxicity, category 2
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>STOT RE 1</b>	Specific target organ toxicity - repeated exposure, category 1
<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>Eye Irrit. 2</b>	Eye irritation, category 2

**236 Maddington Road Maddington 6109**  
**Western Australia**  
**Ph: 08 9493 7948 Fax: 08 9493 2414**  
**Email: ozgel@iinet.net.au**  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 14  
Dated 18/09/2015  
Printed on 25/07/2017  
Page n. 13/14

## 10279-10280 - 1940 BUMPER FLEX

<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H226</b>	Flammable liquid and vapour.
<b>H360D</b>	May damage the unborn child.
<b>H361d</b>	Suspected of damaging the unborn child.
<b>H300</b>	Fatal if swallowed.
<b>H332</b>	Harmful if inhaled.
<b>H372</b>	Causes damage to organs through prolonged or repeated exposure.
<b>H318</b>	Causes serious eye damage.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H412</b>	Harmful to aquatic life with long lasting effects.

### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labelling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

### GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
  4. Regulation (EU) 2015/830 of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - ECHA website

**236 Maddington Road Maddington 6109**  
**Western Australia**  
**Ph: 08 9493 7948 Fax: 08 9493 2414**  
**Email: ozgel@iinet.net.au**  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 14  
Dated 18/09/2015  
Printed on 25/07/2017  
Page n. 14/14

## **10279-10280 - 1940 BUMPER FLEX**

### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

### Changes to previous review:

The following sections were modified:

03 / 08 / 11 / 12 / 15 / 16.