

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 17
Dated 19/10/2016
Printed on 29/08/17
Page n. 1/16

20550-20560 – 1942 TEXTURED PAINT

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 20550-20560
Product name: 1942 TEXTURED PAINT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: ONE-COMPONENT TEXTURED PAINT FOR BUMPERS AND PLASTIC PARTS

1.3. Details of the supplier of the safety data sheet

Name: GELSON SRL
Full address: Via Varese 11/13
District and Country: 20020 Lainate (MI)
Italia
Tel. +39 02 9370640
Fax +39 02 93797341

e-mail address of the competent person responsible for the Safety Data Sheet: info@gelson.it

Australian distributor: OZ-GEL.
236 Maddington Rd
Maddington 6109 Western Australia
Australian distributor phone number: 0418 913 426 (general information)
Local Distributor:

1.4. Emergency telephone number

For urgent inquiries refer to: POISONS INFORMATION CENTRE
Australia Tel. 13 11 26
New Zealand Tel. 0800 764 766

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Reproductive toxicity, effects on or via lactation	H362	May cause harm to breast-fed children.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, acute toxicity, category 1	H400	Very toxic to aquatic life.
Hazardous to the aquatic environment, chronic toxicity, category 2	H411	Toxic to aquatic life with long lasting effects.

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 17
Dated 19/10/2016
Printed on 29/08/17
Page n. 2/16

20550-20560 – 1942 TEXTURED PAINT

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Warning

Hazard statements:

H226	Flammable liquid and vapour.
H362	May cause harm to breast-fed children.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
EUH205	Contains epoxy constituents. May produce an allergic reaction.

Precautionary statements:

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P280	Wear protective gloves / eye protection / face protection.
P304+P340	IF INHALED: remove person to fresh air and keep comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice / attention.

Contains: chlorinated paraffins, C14-17
N-BUTYL ACETATE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 17
Dated 19/10/2016
Printed on 29/08/17
Page n. 3/16

20550-20560 – 1942 TEXTURED PAINT

Identification	Conc. %	Classification 1272/2008 (CLP)
XYLENE (MIXTURE OF ISOMERS)		
CAS 1330-20-7	30 - 50	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Note C
EC 215-535-7		
INDEX 601-022-00-9		
Reg. no. 01-2119486136-34		
N-BUTYL ACETATE		
CAS 123-86-4	20 - 30	Flam. Liq. 3 H226, STOT SE 3 H336, EUH066
EC 204-658-1		
INDEX 607-025-00-1		
Reg. no. 01-2119485493-29		
chlorinated paraffins, C14-17		
CAS 85535-85-9	0,5 - 1	Lact. H362, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=10, EUH066
EC 287-477-0		
INDEX 602-095-00-X		
Reg. no. 01-2119519269-33-0002		

Note: Upper limit is not included into the range

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by the contained substances, see section 11.

4.3. Indication of any immediate medical attention and special treatment needed

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 17
Dated 19/10/2016
Printed on 29/08/17
Page n. 4/16

20550-20560 – 1942 TEXTURED PAINT

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 17
Dated 19/10/2016
Printed on 29/08/17
Page n. 5/16

20550-20560 – 1942 TEXTURED PAINT

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Databank of the social and Economic Concil of Netherlands (SER) Values, AF 2011:18
EU	OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2016

236 Maddington Road Maddington 6109
 Western Australia
 Ph: 08 9493 7948 Fax: 08 9493 2414
 Email: ozgel@iinet.net.au
 A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
 ABN: 38 926 088 116



Revision nr. 17
 Dated 19/10/2016
 Printed on 29/08/17
 Page n. 6/16

20550-20560 – 1942 TEXTURED PAINT

XYLENE (MIXTURE OF ISOMERS)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
VLA	ESP	221	50	442	100	SKIN
VLEP	FRA	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	
TLV	ITA	221	50	442	100	SKIN
OEL	NLD	210		442		SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

N-BUTYL ACETATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
MAK	DEU	480	100	960	200
VLA	ESP	724	150	965	200
VLEP	FRA	710	150	940	200
WEL	GBR	724	150	966	200
OEL	NLD	150			
TLV-ACGIH		713	150	950	200

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,18	mg/l
Normal value in marine water	0,01	mg/l
Normal value for fresh water sediment	0,98	mg/kg
Normal value for marine water sediment	0,09	mg/kg
Normal value for water, intermittent release	0,36	mg/l
Normal value of STP microorganisms	35,6	mg/l
Normal value for the terrestrial compartment	0,09	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation	859,7 mg/m3	859,7 mg/m3	102,34 mg/m3	102,34 mg/m3	960 mg/m3	960 mg/m3	480 mg/m3	480 mg/m3

chlorinated paraffins, C14-17

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,001	mg/l
Normal value in marine water	0,0002	mg/l
Normal value for fresh water sediment	13	mg/kg
Normal value for marine water sediment	2,6	mg/kg

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 17
Dated 19/10/2016
Printed on 29/08/17
Page n. 7/16

20550-20560 – 1942 TEXTURED PAINT

Normal value of STP microorganisms	80	mg/l
Normal value for the food chain (secondary poisoning)	10	mg/kg
Normal value for the terrestrial compartment	20	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	0,115 mg/kg				
Inhalation			VND	0,4 mg/m3			VND	1,6 mg/m3
Skin			VND	5,75 mg/kg			VND	11,5 mg/kg

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 17
Dated 19/10/2016
Printed on 29/08/17
Page n. 8/16

20550-20560 – 1942 TEXTURED PAINT

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	viscous liquid
Colour	vari colori
Odour	solvent
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	26 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	1,040 Kg/l
Solubility	soluble in organic solvents
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

VOC (Directive 2004/42/EC) :	62,65 %	-	651,52	g/litre
VOC (volatile carbon) :	48,20 %	-	501,30	g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

N-BUTYL ACETATE: decomposes readily with water, especially when warm.

10.2. Chemical stability

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 17
Dated 19/10/2016
Printed on 29/08/17
Page n. 9/16

20550-20560 – 1942 TEXTURED PAINT

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.
N-BUTYL ACETATE: risk of explosion on contact with: strong oxidising agents. Can react dangerously with alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with the air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

N-BUTYL ACETATE: avoid exposure to moisture, sources of heat and naked flames.

10.5. Incompatible materials

N-BUTYL ACETATE: water, nitrates, strong oxidising agents, acids and alkalis and potassium tert-butoxide.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

11.1. Information on toxicological effects

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product must be handled carefully because of its possible negative effects on children during the breast-feeding period.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin. Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

This product contains highly volatile substances, which may cause serious depression of the central nervous system (CNS) and have negative effects, such as drowsiness, dizziness, slow reflexes, narcosis.

This product contains epoxy resins. Producer's specifications are as follows: Because of epoxy-product properties and according to the toxicological data available for similar products, this preparation may sensitize and irritate the skin and the respiratory system. It contains epoxy components at low molecular weights, which may irritate eyes, mucosae and skin. Frequent contact with skin may cause irritation and sensitization phenomena. Sensitization reactions may also be caused by other epoxy components (cross-sensitization). Avoid contact with skin and exposure to vapours and aerosols.

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 17
Dated 19/10/2016
Printed on 29/08/17
Page n. 10/16

20550-20560 – 1942 TEXTURED PAINT

N-BUTYL ACETATE: in humans the substance's vapours cause irritation to the eyes and nose. In the event of repeated exposure, there is skin irritation, dermatosis (with dryness and flaking of the skin) and keratitis.

chlorinated paraffins, C14-17
LD50 (Oral) > 2000 mg/kg Ratto
LD50 (Dermal) 4000 mg/kg Ratto
LC50 (Inhalation) > 12042 mg/m³/4h Ratto

XYLENE (MIXTURE OF ISOMERS)
LD50 (Oral) 3523 mg/kg Rat
LD50 (Dermal) 4350 mg/kg Rabbit
LC50 (Inhalation) 26 mg/l/4h Rat

N-BUTYL ACETATE
LD50 (Oral) > 6400 mg/kg Rat
LD50 (Dermal) > 5000 mg/kg Rabbit
LC50 (Inhalation) 21,1 mg/l/4h Rat

SECTION 12. Ecological information

This product is dangerous for the environment and highly toxic for aquatic organisms.

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

chlorinated paraffins, C14-17	
LC50 - for Fish	> 5000 mg/l/96h <i>Alburnus alburnus</i>
EC50 - for Crustacea	0,0059 mg/l/48h <i>Daphnia magna</i>
EC50 - for Algae / Aquatic Plants	> 3,2 mg/l/72h
Chronic NOEC for Fish	> 0,125 mg/l <i>Alburnus alburnus</i>
Chronic NOEC for Crustacea	0,01 mg/l <i>Daphnia</i>

12.2. Persistence and degradability

chlorinated paraffins, C14-17	
Solubility in water	0,0027 mg/l
Rapidly degradable	

XYLENE (MIXTURE OF ISOMERS)	
Solubility in water	mg/l 100 - 1000
Degradability: information not available	

N-BUTYL ACETATE	
Solubility in water	mg/l 1000 - 10000
Rapidly degradable	

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 17
Dated 19/10/2016
Printed on 29/08/17
Page n. 11/16

20550-20560 – 1942 TEXTURED PAINT

12.3. Bioaccumulative potential

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: n-octanol/water 3,12
BCF 25,9

N-BUTYL ACETATE

Partition coefficient: n-octanol/water 2,3
BCF 15,3

12.4. Mobility in soil

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: soil/water 2,73

N-BUTYL ACETATE

Partition coefficient: soil/water < 3

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 17
Dated 19/10/2016
Printed on 29/08/17
Page n. 12/16

20550-20560 – 1942 TEXTURED PAINT

14.1. UN number

ADR / RID, IMDG, 1263
IATA:

14.2. UN proper shipping name

ADR / RID: PAINT
IMDG: PAINT
(chlorinated
paraffins, C14-
17)
IATA: PAINT

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3
IMDG: Class: 3 Label: 3
IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, III
IATA:

14.5. Environmental hazards

ADR / RID: Environmentally
Hazardous
IMDG: Marine Pollutant
IATA: NO



For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	Special Provision: - EMS: F-E, <u>S-E</u>	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 220	Packaging instructions:

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@inet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 17
Dated 19/10/2016
Printed on 29/08/17
Page n. 13/16

20550-20560 – 1942 TEXTURED PAINT

Pass.:

L
Maximum
quantity: 60 L

366
Packaging
instructions:
355

Special Instructions:

A3, A72

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso category 9i, 6

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point 3 - 40

Substances in Candidate List (Art. 59 REACH)

None

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) :

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@inet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 17
Dated 19/10/2016
Printed on 29/08/17
Page n. 14/16

20550-20560 – 1942 TEXTURED PAINT

Special finishes.

VOC given in g/litre of product in a
ready-to-use condition :

Limit value: 840,00

VOC of product : 711,04

- Thinned with : 30,00 %

PLASTIC PAINT
SYSTEM 1900 -
DILUENTE

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Lact.	Reproductive toxicity, effects on or via lactation
Acute Tox. 4	Acute toxicity, category 4
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H226	Flammable liquid and vapour.
H362	May cause harm to breast-fed children.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH205	Contains epoxy constituents. May produce an allergic reaction.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labelling of chemicals

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414

Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 17
Dated 19/10/2016
Printed on 29/08/17
Page n. 15/16

20550-20560 – 1942 TEXTURED PAINT

- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

09.