

236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 6  
Dated 24/07/2015  
Printed on 08/08/2017  
Page n. 1/12

## 45770 - DEFENDER CATALYST

# Safety data sheet

## SECTION 1. Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Code: 45770  
Product name DEFENDER CATALYST

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Catalyst for paint conditioner

### 1.3. Details of the supplier of the safety data sheet

Name GELSON SRL  
Full address Via Varese 11/13  
District and Country 20020 Lainate (MI)  
Italia  
Tel. +39 02 9370640  
Fax +39 02 93797341

e-mail address of the competent person responsible for the Safety Data Sheet info@gelson.it

Australian distributor OZ-GEL  
236 Maddington Rd  
Maddington 6109 Western Australia  
ozgel@iinet.net.au

Australian distributor phone number  
Local Distributor 0418 913 426 (general information)

### 1.4. Emergency telephone number

For urgent inquiries refer to  
POISONS INFORMATION CENTRE  
Australia Tel. 13 11 26  
New Zealand Tel. 0800 764 766

## SECTION 2. Hazards identification.

### 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

#### Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 2	H371	May cause damage to organs.
Hazardous to the aquatic environment, acute toxicity, category 1	H400	Very toxic to aquatic life.
Hazardous to the aquatic environment, chronic toxicity, category 1	H410	Very toxic to aquatic life with long lasting effects.

### 2.2. Label elements.

236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 6  
Dated 24/07/2015  
Printed on 08/08/2017  
Page n. 2/12

## 45770 - DEFENDER CATALYST

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.



Signal words:

Danger

Hazard statements:

<b>H225</b>	Highly flammable liquid and vapour.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H371</b>	May cause damage to organs.
<b>H410</b>	Very toxic to aquatic life with long lasting effects.

Precautionary statements:

<b>P210</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>P233</b>	Keep container tightly closed.
<b>P264</b>	Wash . . . thoroughly after handling.
<b>P280</b>	Wear protective gloves / eye protection / face protection.
<b>P303+P361+P353</b>	IF ON SKIN (or hair): take off immediately all contaminated clothing. Rinse skin with water / shower.
<b>P308+P311</b>	IF exposed or concerned: call a POISON CENTER / doctor / . . .

**Contains:** METHANOL

### 2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

## SECTION 3. Composition/information on ingredients.

### 3.1. Substances.

Information not relevant.

### 3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification 1272/2008 (CLP).
<b>polidimetilsilossano aminofunzionale con terminazione metossi</b> CAS. 69430-37-1	50 - 100	Flam. Liq. 2 H225, Eye Irrit. 2 H319, Skin Irrit. 2 H315, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410

EC. -

INDEX. -

**METHANOL**

236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 6  
Dated 24/07/2015  
Printed on 08/08/2017  
Page n. 3/12

## 45770 - DEFENDER CATALYST

CAS. 67-56-1	3 - 5	Flam. Liq. 2 H225, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT SE 1 H370
EC. 200-659-6		
INDEX. 603-001-00-X		
<b>Ottametilciclotetrasilossano</b>		
CAS. 556-67-2	0,5 - 1	Flam. Liq. 3 H226, Repr. 2 H361f, Aquatic Chronic 4 H413
EC. 209-136-7		
INDEX. 014-018-00-1		

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

### SECTION 4. First aid measures.

#### 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

#### 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

#### 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

### SECTION 5. Firefighting measures.

#### 5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

#### 5.2. Special hazards arising from the substance or mixture.

236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 6  
Dated 24/07/2015  
Printed on 08/08/2017  
Page n. 4/12

## 45770 - DEFENDER CATALYST

### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

#### 5.3. Advice for firefighters.

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures.

#### 6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage.

#### 7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the

236 Maddington Road Maddington 6109  
 Western Australia  
 Ph: 08 9493 7948 Fax: 08 9493 2414  
 Email: ozgel@inet.net.au  
 A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
 ABN: 38 926 088 116



Revision nr. 6  
 Dated 24/07/2015  
 Printed on 08/08/2017  
 Page n. 5/12

## 45770 - DEFENDER CATALYST

product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s).

Information not available.

## SECTION 8. Exposure controls/personal protection.

### 8.1. Control parameters.

Regulatory References:

AUS	Österreich	Grenzwerteverordnung 2011 - GKV 2011
BEL	Belgique	AR du 11/3/2002. La liste est mise à jour pour 2010
DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GRB	United Kingdom	EH40/2005 Workplace exposure limits
IRL	Éire	Code of Practice Chemical Agent Regulations 2011
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Databank of the social and Economic Concil of Netherlands (SER) Values, AF 2011:18
EU	OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.
	TLV-ACGIH	ACGIH 2014

### METHANOL

#### Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
MAK	AUS	260	200	1040	800	SKIN.
VLEP	BEL	266	200	333	250	SKIN.
AGW	DEU	270	200	1080	800	SKIN.
MAK	DEU	270	200	1080	800	SKIN.
VLA	ESP	266	200			SKIN.
VLEP	FRA	260	200	1300	1000	SKIN.
WEL	GRB	266	200	333	250	SKIN.
OEL	IRL	260	200			SKIN.
TLV	ITA	260	200			SKIN.
OEL	NLD	133	100			SKIN.
OEL	EU	260	200			SKIN.
TLV-ACGIH		262	200	328	250	

236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 6  
Dated 24/07/2015  
Printed on 08/08/2017  
Page n. 6/12

## 45770 - DEFENDER CATALYST

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

## SECTION 9. Physical and chemical properties.

### 9.1. Information on basic physical and chemical properties.

Appearance	liquid
Colour	yellowish
Odour	amino
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	Not available.
Initial boiling point.	> 35 °C.
Boiling range.	Not available.
Flash point.	15,5 °C.
Evaporation rate	Not available.

236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@inet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 6  
Dated 24/07/2015  
Printed on 08/08/2017  
Page n. 7/12

## 45770 - DEFENDER CATALYST

Flammability (solid, gas)	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	0,986 Kg/l
Solubility	insoluble in water
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	390 °C.
Decomposition temperature.	> 200°C
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

### 9.2. Other information.

VOC (Directive 1999/13/EC) :	5,00 % - 49,30 g/litre.
VOC (volatile carbon) :	1,82 % - 17,96 g/litre.

## SECTION 10. Stability and reactivity.

### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions.

The vapours may also form explosive mixtures with the air.

### 10.4. Conditions to avoid.

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

### 10.5. Incompatible materials.

Information not available.

### 10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 6  
Dated 24/07/2015  
Printed on 08/08/2017  
Page n. 8/12

## 45770 - DEFENDER CATALYST

### SECTION 11. Toxicological information.

#### 11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation. Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin. Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

This product may cause irreversible, non-lethal damages after a single exposure by inhalation, cutaneous absorption and ingestion.

METHANOL: The minimal lethal dose following ingestion is considered to be in the range of 300-1000 mg/kg. Ingestion of as little as 4-10 ml methanol in adults may cause permanent blindness (IPCS).

### SECTION 12. Ecological information.

This product is dangerous for the environment and highly toxic for aquatic organisms. In the long term, it has negative effects on aquatic environment.

#### 12.1. Toxicity.

Information not available.

#### 12.2. Persistence and degradability.

METHANOL

Solubility in water. mg/l 1000 - 10000

Rapidly biodegradable.

#### 12.3. Bioaccumulative potential.

METHANOL

Partition coefficient: n-octanol/water. -0,77

BCF. 0,2

#### 12.4. Mobility in soil.

Information not available.

#### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

#### 12.6. Other adverse effects.

Information not available.



236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 6  
Dated 24/07/2015  
Printed on 08/08/2017  
Page n. 9/12

## 45770 - DEFENDER CATALYST

### SECTION 13. Disposal considerations.

#### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

#### CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

### SECTION 14. Transport information.

#### 14.1. UN number.

ADR / RID, IMDG, IATA: 1993

#### 14.2. UN proper shipping name.

ADR / RID: FLAMMABLE  
LIQUID,  
(Aminomethoxy-  
polydimethylsiloxane,  
methanol)  
IMDG: FLAMMABLE  
LIQUID, N.O.S.  
IATA: FLAMMABLE  
LIQUID, N.O.S.

#### 14.3. Transport hazard class(es).

ADR / RID: Class: 3 Label: 3  
IMDG: Class: 3 Label: 3  
IATA: Class: 3 Label: 3



#### 14.4. Packing group.

ADR / RID, IMDG, IATA: II

#### 14.5. Environmental hazards.

ADR / RID: Environmentally  
Hazardous.  
IMDG: Marine Pollutant.  
IATA: NO



236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 6  
Dated 24/07/2015  
Printed on 08/08/2017  
Page n. 10/12

## 45770 - DEFENDER CATALYST

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

### 14.6. Special precautions for user.

ADR / RID:	HIN - Kemler: 33	Limited Quantities 1 L	Tunnel restriction code (D/E)
IMDG:	Special Provision: - EMS: F-E, S-E,	Limited Quantities 1 L	
IATA:	Cargo:	Maximum quantity: 60 L	Packaging instructions: 364
	Pass.:	Maximum quantity: 5 L	Packaging instructions: 353
	Special Instructions:	A3	

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

## SECTION 15. Regulatory information.

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category. 7b, 9i

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product Point. 3 - 40

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 6  
Dated 24/07/2015  
Printed on 08/08/2017  
Page n. 11/12

## 45770 - DEFENDER CATALYST

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

### 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

## SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Flam. Liq. 3</b>	Reproductive toxicity, category 2
<b>Acute Tox. 3</b>	Acute toxicity, category 3
<b>STOT SE 1</b>	Specific target organ toxicity - single exposure, category 1
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 2</b>	Specific target organ toxicity - single exposure, category 2
<b>Aquatic Acute 1</b>	Hazardous to the aquatic environment, acute toxicity, category 1
<b>Aquatic Chronic 1</b>	Hazardous to the aquatic environment, chronic toxicity, category 1
<b>Aquatic Chronic 4</b>	Hazardous to the aquatic environment, chronic toxicity, category 4
<b>H225</b>	Highly flammable liquid and vapour.
<b>H226</b>	Flammable liquid and vapour.
<b>H361f</b>	Suspected of damaging fertility.
<b>H301</b>	Toxic if swallowed.
<b>H311</b>	Toxic in contact with skin.
<b>H331</b>	Toxic if inhaled.
<b>H370</b>	Causes damage to organs.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H371</b>	May cause damage to organs.
<b>H400</b>	Very toxic to aquatic life.
<b>H410</b>	Very toxic to aquatic life with long lasting effects.
<b>H413</b>	May cause long lasting harmful effects to aquatic life.

### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%

**236 Maddington Road Maddington 6109**  
**Western Australia**  
**Ph: 08 9493 7948 Fax: 08 9493 2414**  
**Email: ozgel@iinet.net.au**  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 6  
Dated 24/07/2015  
Printed on 08/08/2017  
Page n. 12/12

## 45770 - DEFENDER CATALYST

- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

### GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
  4. Regulation (EU) 2015/830 of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - ECHA website

### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.  
This document must not be regarded as a guarantee on any specific product property.  
The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.  
Provide appointed staff with adequate training on how to use chemical products.

### Changes to previous review:

The following sections were modified:  
01 / 02 / 08 / 12 / 14.