

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 1
Dated 14/10/2016
Printed on 08/08/2017
Page n. 1/12

45780-45790 - DEFENDER CLEANER

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 45780-45790
Product name: DEFENDER CLEANER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Cleaning pre-treatment

1.3. Details of the supplier of the safety data sheet

Name: GELSON SRL
Full address: Via Varese 11/13
District and Country: 20020 Lainate (MI) Italia
Tel. +39 02 9370640
Fax +39 02 93797341

e-mail address of the competent person responsible for the Safety Data Sheet: info@gelson.it

Australian distributor: OZ-GEL
236 Maddington Rd
Maddington 6109 Western Australia
ozgel@iinet.net.au

Australian distributor phone number: 0418 913 426 (general information)
Local Distributor:

1.4. Emergency telephone number

For urgent inquiries refer to: POISONS INFORMATION CENTRE
Australia Tel. 13 11 26
New Zealand Tel. 0800 764 766

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Eye irritation, category 2	H319	Causes serious eye irritation.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@inet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 1
Dated 14/10/2016
Printed on 08/08/2017
Page n. 2/12

45780-45790 - DEFENDER CLEANER



Signal words:

Warning

Hazard statements:

H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P264 Wash . . . thoroughly after handling.
P280 Wear protective gloves / eye protection / face protection.
P303+P361+P353 IF ON SKIN (or hair): take off immediately all contaminated clothing. Rinse skin with water / shower.
P337+P313 If eye irritation persists: Get medical advice / attention.

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification 1272/2008 (CLP).
PROPAN-2-OL CAS. 67-63-0 EC. 200-661-7 INDEX. 603-117-00-0 Reg. no. 01-2119457558-25	10 - 20	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336
1-PROPOSSIPROPAN-2-OLO CAS. 1569-01-3 EC. 216-372-4 INDEX. - Reg. no. 01-2119474443-37-0000	1 - 5	Flam. Liq. 3 H226, Eye Irrit. 2 H319

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 1
Dated 14/10/2016
Printed on 08/08/2017
Page n. 3/12

45780-45790 - DEFENDER CLEANER

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 1
Dated 14/10/2016
Printed on 08/08/2017
Page n. 4/12

45780-45790 - DEFENDER CLEANER

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

236 Maddington Road Maddington 6109
 Western Australia
 Ph: 08 9493 7948 Fax: 08 9493 2414
 Email: ozgel@iinet.net.au
 A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
 ABN: 38 926 088 116



Revision nr. 1
 Dated 14/10/2016
 Printed on 08/08/2017
 Page n. 5/12

45780-45790 - DEFENDER CLEANER

8.1. Control parameters.

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
NLD	Nederland	Databank of the social and Economic Council of Netherlands (SER) Values, AF 2011:18
	TLV-ACGIH	ACGIH 2014

PROPAN-2-OL

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	500	200	1000	400
MAK	DEU	500	200	1000	400
VLA	ESP	500	200	1000	400
VLEP	FRA			980	400
WEL	GBR	999	400	1250	500
OEL	NLD	650			
TLV-ACGIH		492	200	983	400

Predicted no-effect concentration - PNEC.

Normal value in fresh water	140,9	mg/l
Normal value in marine water	140,9	mg/l
Normal value for fresh water sediment	552	mg/kg
Normal value for marine water sediment	552	mg/kg
Normal value for water, intermittent release	140,9	mg/l
Normal value of STP microorganisms	2251	mg/l
Normal value for the food chain (secondary poisoning)	160	mg/kg
Normal value for the terrestrial compartment	28	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers.			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.			VND	26 mg/kg				
Inhalation.			VND	89 mg/m3			VND	500 mg/m3
Skin.			VND	319 mg/kg			VND	888 mg/kg

1-PROPOSSIPROPAN-2-OLO

Predicted no-effect concentration - PNEC.

Normal value in fresh water	0,1	mg/l
Normal value in marine water	0,01	mg/l
Normal value for fresh water sediment	0,386	mg/kg/d
Normal value for marine water sediment	0,0386	mg/kg/d
Normal value for water, intermittent release	1	mg/l
Normal value of STP microorganisms	4	mg/l
Normal value for the terrestrial compartment	0,0185	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers.			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.			VND	2,2 mg/kg bw/d				
Inhalation.			VND	26 mg/m3 1h			VND	217 mg/m3

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 1
Dated 14/10/2016
Printed on 08/08/2017
Page n. 6/12

45780-45790 - DEFENDER CLEANER

Skin.	VND	2,2 mg/kg bw/d	VND	9 mg/kg bw/d
-------	-----	-------------------	-----	--------------

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance	liquid
Colour	red
Odour	characteristic
Odour threshold.	Not available.
pH.	9,75
Melting point / freezing point.	Not available.
Initial boiling point.	> 35 °C.
Boiling range.	Not available.

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 1
Dated 14/10/2016
Printed on 08/08/2017
Page n. 7/12

45780-45790 - DEFENDER CLEANER

Flash point.	28 °C.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	18,51 mmHg
Vapour density	Not available.
Relative density.	0,948 Kg/l
Solubility	soluble in water
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information.

VOC (Directive 2004/42/EC) :	21,90 % - 207,64 g/litre.
VOC (volatile carbon) :	20,50 % - 194,33 g/litre.

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

The vapours may also form explosive mixtures with the air.

10.4. Conditions to avoid.

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials.

Information not available.

10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 1
Dated 14/10/2016
Printed on 08/08/2017
Page n. 8/12

45780-45790 - DEFENDER CLEANER

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation. Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

1-PROPOSSIPROPAN-2-OLO
LD50 (Oral).> 2000 mg/kg ratto
LD50 (Dermal).> 2000 mg/kg coniglio
LC50 (Inhalation).8,34 mg/l/4h

PROPAN-2-OL
LD50 (Oral).4710 mg/kg Rat
LD50 (Dermal).12800 mg/kg Rat
LC50 (Inhalation).72,6 mg/l/4h Rat

SECTION 12. Ecological information.

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity.

1-PROPOSSIPROPAN-2-
OLO
LC50 - for Fish. > 100 mg/l/96h Pesci
EC50 - for Crustacea. > 100 mg/l/48h
EC50 - for Algae / Aquatic
Plants. 1,466 mg/l/72h

PROPAN-2-OL
LC50 - for Fish. > 1000 mg/l/96h
EC50 - for Crustacea. > 1000 mg/l/48h

12.2. Persistence and degradability.

1-PROPOSSIPROPAN-2-
OLO
Rapidly biodegradable.

PROPAN-2-OL
Rapidly biodegradable.

12.3. Bioaccumulative potential.

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@inet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 1
Dated 14/10/2016
Printed on 08/08/2017
Page n. 9/12

45780-45790 - DEFENDER CLEANER

1-PROPOSSIPROPAN-2-
OLO
Partition coefficient: n-
octanol/water. 0,621 Log Kow calculato

PROPAN-2-OL
Partition coefficient: n-
octanol/water. 0,05

12.4. Mobility in soil.

1-PROPOSSIPROPAN-2-
OLO
Partition coefficient:
soil/water. 1,5

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

ADR / RID, IMDG, 1987
IATA:

14.2. UN proper shipping name.

ADR / RID: ALCOHOLS,
N.O.S.
(PROPAN-2-OL,
1-PROPOXY-2-
PROPANOL)
IMDG: ALCOHOLS,
N.O.S.

236 Maddington Road Maddington 6109
 Western Australia
 Ph: 08 9493 7948 Fax: 08 9493 2414
 Email: ozgel@iinet.net.au
 A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
 ABN: 38 926 088 116



Revision nr. 1
 Dated 14/10/2016
 Printed on 08/08/2017
 Page n. 10/12

45780-45790 - DEFENDER CLEANER

IATA: (PROPAN-2-OL,
 1-PROPOXY-2-
 PROPANOL)
 ALCOHOLS,
 N.O.S.
 (PROPAN-2-OL,
 1-PROPOXY-2-
 PROPANOL)

14.3. Transport hazard class(es).

ADR / RID: Class: 3 Label: 3
 IMDG: Class: 3 Label: 3
 IATA: Class: 3 Label: 3



14.4. Packing group.

ADR / RID, IMDG, III
 IATA:

14.5. Environmental hazards.

ADR / RID: NO
 IMDG: NO
 IATA: NO

14.6. Special precautions for user.

ADR / RID:	HIN - Kemler: 30	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
	Special Provision: -		
IMDG:	EMS: F-E, S-D	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 220 L	Packaging instructions: 366
	Pass.:	Maximum quantity: 60 L	Packaging instructions: 355
	Special Instructions:	A3, A180	

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@inet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 1
Dated 14/10/2016
Printed on 08/08/2017
Page n. 11/12

45780-45790 - DEFENDER CLEANER

Seveso category. 6

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product
Point. 3 - 40

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) :

Preparatory and cleaning - preparatory products.

VOC given in g/litre of product in a
ready-to-use condition :

Limit value: 850,00

VOC of product : 207,64

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2 Flammable liquid, category 2

Flam. Liq. 3 Flammable liquid, category 3

Eye Irrit. 2 Eye irritation, category 2

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414

Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 1
Dated 14/10/2016
Printed on 08/08/2017
Page n. 12/12

45780-45790 - DEFENDER CLEANER

STOT SE 3	Specific target organ toxicity - single exposure, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labelling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.