

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 13
Dated 07/07/2016
Printed on 29/08/17
Page n. 1/17

30564 - GELFLEX 333 NERO

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 30564
Product name: GELFLEX 333 NERO

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: One-component polyurethane sealant

1.3. Details of the supplier of the safety data sheet

Name: GELSON SRL
Full address: Via Varese 11/13
District and Country: 20020 Lainate (MI) Italia
Tel. +39 02 9370640
Fax +39 02 93797341

e-mail address of the competent person responsible for the Safety Data Sheet: info@gelson.it

Australian distributor: OZ-GEL.
236 Maddington Rd
Maddington 6109 Western Australia
Australian distributor phone number: 0418 913 426 (general information)
Local Distributor:

1.4. Emergency telephone number

For urgent inquiries refer to: POISONS INFORMATION CENTRE
Australia Tel. 13 11 26
New Zealand Tel. 0800 764 766

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:
Respiratory sensitization, category 1

H334

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

2.2. Label elements

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 13
Dated 07/07/2016
Printed on 29/08/17
Page n. 2/17

30564 - GELFLEX 333 NERO

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
EUH204 Contains isocyanates. May produce an allergic reaction.
EUH208 Contains:
DIPHENYLMETHANE-4,4'-DIISOCYANATE, DIPHENYLMETHANE-4,4'-DIISOCYANATE

May produce an allergic reaction.

Precautionary statements:

P284 [In case of inadequate ventilation] wear respiratory protection.
P304+P340 IF INHALED: remove person to fresh air and keep comfortable for breathing.
P342+P311 If experiencing respiratory symptoms: call a POISON CENTER / doctor / . . .

Contains: DIPHENYLMETHANE-4,4'-DIISOCYANATE
DIPHENYLMETHANE-4,4'-DIISOCYANATE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	Conc. %	Classification 1272/2008 (CLP)
XYLENE (MIXTURE OF ISOMERS)		

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 13
Dated 07/07/2016
Printed on 29/08/17
Page n. 3/17

30564 - GELFLEX 333 NERO

CAS 1330-20-7	5 - 9	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Note C
EC 215-535-7		
INDEX 601-022-00-9		
Reg. no. 01-2119486136-34		
ETHYL ACETATE		
CAS 141-78-6	1 - 5	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC 205-500-4		
INDEX 607-022-00-5		
Reg. no. 01-2119475103-46		
DIPHENYLMETHANE-4,4'-DIISOCYANATE		
CAS 9016-87-9	0,5 - 1	Carc. 2 H351, Acute Tox. 4 H332, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317, Note 2 C
EC 202-966-0		
INDEX 615-005-00-9		
DIPHENYLMETHANE-4,4'-DIISOCYANATE		
CAS 101-68-8	0,5 - 1	Carc. 2 H351, Acute Tox. 4 H332, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317, Note 2 C
EC 202-966-0		
INDEX 615-005-00-9		
Reg. no. 01-2119457014-47		
PHOSPHORIC ACID		
CAS 7664-38-2	0 - 0,5	Skin Corr. 1B H314, Note B
EC 231-633-2		
INDEX 015-011-00-6		

Note: Upper limit is not included into the range

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 13
Dated 07/07/2016
Printed on 29/08/17
Page n. 4/17

30564 - GELFLEX 333 NERO

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by the contained substances, see section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 13
Dated 07/07/2016
Printed on 29/08/17
Page n. 5/17

30564 - GELFLEX 333 NERO

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

236 Maddington Road Maddington 6109
 Western Australia
 Ph: 08 9493 7948 Fax: 08 9493 2414
 Email: ozgel@inet.net.au
 A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
 ABN: 38 926 088 116



Revision nr. 13
 Dated 07/07/2016
 Printed on 29/08/17
 Page n. 6/17

30564 - GELFLEX 333 NERO

8.1. Control parameters

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Databank of the social and Economic Concil of Netherlands (SER) Values, AF 2011:18
EU	OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2016

XYLENE (MIXTURE OF ISOMERS)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
VLA	ESP	221	50	442	100	SKIN
VLEP	FRA	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	
TLV	ITA	221	50	442	100	SKIN
OEL	NLD	210		442		SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

ETHYL ACETATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	1500	400	3000	800	
MAK	DEU	1500	400	3000	800	
VLA	ESP	1460	400			
VLEP	FRA	1400	400			
WEL	GBR		200		400	
OEL	NLD	550		1100		
TLV-ACGIH		1441	400			

DIPHENYLMETHANE-4,4'-DIISOCYANATE

Threshold Limit Value

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@inet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 13
Dated 07/07/2016
Printed on 29/08/17
Page n. 7/17

30564 - GELFLEX 333 NERO

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
MAK	DEU	0,05		0,05	
VLA	ESP		0,005		
VLEP	FRA	0,1		0,2	
WEL	GBR	0,02		0,07	
TLV-ACGIH		0,051	0,005		

DIPHENYLMETHANE-4,4'-DIISOCYANATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	0,05		0,05		
MAK	DEU	0,05		0,05		SKIN
MAK	DEU	0,05		0,05		INHAL
VLA	ESP	0,052	0,005			
VLEP	FRA	0,1	0,01	0,2	0,02	
TLV-ACGIH		0,051	0,005			

Predicted no-effect concentration - PNEC

Normal value in fresh water		1,1		mg/l
Normal value in marine water		0,11		mg/l
Normal value for fresh water sediment		NEA		
Normal value for marine water sediment		NEA		
Normal value of STP microorganisms		1,1		mg/l
Normal value for the food chain (secondary poisoning)		NEA		
Normal value for the terrestrial compartment		1,1		mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers Acute local	Acute systemic	Chronic local	Chronic systemic	Effects on workers			
					Acute local	Acute systemic	Chronic local	Chronic systemic
Oral	VND	20 mg/kg						
Inhalation	0,05 mg/m3	0,05 mg/m3	0,025 mg/m3	0,025 mg/m3	0,1 mg/m3	0,1 mg/m3	0,05 mg/m3	0,05 mg/m3
Skin	17,2 mg/kg	25 mg/kg			28,7 mg/kg	50 mg/kg		

PHOSPHORIC ACID

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	2		4		INHAL
MAK	DEU	2		4		INHAL
VLA	ESP	1		2		
VLEP	FRA	1	0,2	2	0,5	
WEL	GBR	1		2		

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 13
Dated 07/07/2016
Printed on 29/08/17
Page n. 8/17

30564 - GELFLEX 333 NERO

TLV	ITA	1	2
OEL	NLD	1	2
OEL	EU	1	2
TLV-ACGIH		1	3

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414

Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 13
Dated 07/07/2016
Printed on 29/08/17
Page n. 9/17

30564 - GELFLEX 333 NERO

Appearance	paste
Colour	various
Odour	mild
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	> 60 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	1,270 Kg/l
Solubility	soluble in organic solvents
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	> 250 °C
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

VOC (Directive 2004/42/EC) :	9,60 % - 121,92 g/litre
VOC (volatile carbon) :	8,18 % - 103,85 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

PHOSPHORIC ACID: decomposes at temperatures over 200°C/392°F.

DIPHENYLMETHANE-4,4'-DIISOCYANATE: decomposes at 274°C/525°F. With water it develops carbon dioxide and forms an insoluble solid polymer. Consequently any wet material recovered must be stored in open containers.

DIPHENYLMETHANE-4,4'-DIISOCYANATE: decomposes at 274°C. With water it develops carbon dioxide and forms an insoluble solid polymer. Consequently any wet material recovered must be stored in open containers.

ETHYL ACETATE: decomposes slowly into acetic acid and ethanol under the effect of light, air and water.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 13
Dated 07/07/2016
Printed on 29/08/17
Page n. 10/17

30564 - GELFLEX 333 NERO

PHOSPHORIC ACID: risk of explosion on contact with nitromethane. May react dangerously with alkalis and sodium borohydride.
XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.
DIPHENYLMETHANE-4,4'-DIISOCYANATE: can react dangerously with: alcohols, amines, ammonia, sodium hydroxide, acids, water and strong bases and acids.
DIPHENYLMETHANE-4,4'-DIISOCYANATE: can react dangerously with: alcohols, amines, ammonia, sodium hydroxide, acids, water and strong bases and acids.
ETHYL ACETATE: risk of explosion on contact with: metals, alkalis, hydrides. oleum. can react violently with: fluoride, strong oxidising agents, chlorosulfuric acid, potassium tert-butoxide. Forms explosive mixtures with the air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

ETHYL ACETATE: avoid exposure to light, sources of heat and naked flames.

10.5. Incompatible materials

PHOSPHORIC ACID: Metals, strong alkalis, aldehydes, sulphides and peroxides.

ETHYL ACETATE: acids and bases, strong oxidising agents; aluminium and some plastics, nitrates and chlorosulphuric acid.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

PHOSPHORIC ACID: phosphorus oxide.

DIPHENYLMETHANE-4,4'-DIISOCYANATE: nitric oxides, carbon oxides, hydrogen cyanide.

DIPHENYLMETHANE-4,4'-DIISOCYANATE: nitric oxides, carbon oxides, hydrogen cyanide.

SECTION 11. Toxicological information

11.1. Information on toxicological effects

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

Inhalation of this product causes sensitization, which may then give rise to a series of inflammatory episodes, most of all characterized by obstruction and affecting the respiratory system. Sometimes, sensitization phenomena arise together with evident rhinitis and asthma. Damages to the respiratory system depend on the inhaled quantity, on the product concentration in the working environment and on the exposure time.

This product contains isocyanates. Producer's specifications are as follows: Ready-to-use products containing isocyanates may irritate mucosas, particularly those of the respiratory system, and may give rise to hypersensitivity reactions. Vapour or aerosol inhalation may lead to sensitization. Please take all the measures used for all solvent-containing products while manipulating isocyanate-containing products. Avoid vapour and aerosol inhalation. People with allergic or asthmatic precedents or subject to respiratory disorders should not handle products containing isocyanates.

This product contains sensitizing substance/s and may cause allergic reactions.

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414

Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 13
Dated 07/07/2016
Printed on 29/08/17
Page n. 11/17

30564 - GELFLEX 333 NERO

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

DIPHENYLMETHANE-4,4'-DIISOCYANATE: risk of sensitization even at concentrations lower than TLV in case of spray working.

DIFENILMETAN-4,4'-DIISOCIANATO: rischio di sensibilizzazione anche a concentrazioni inferiori al TLV in caso di esecuzione di lavori a spruzzo.

PHOSPHORIC ACID

LD50 (Oral)1530 mg/kg Rat

LD50 (Dermal)2740 mg/kg Rabbit

LC50 (Inhalation)> 0,85 mg/l/1h Rat

XYLENE (MIXTURE OF ISOMERS)

LD50 (Oral)3523 mg/kg Rat

LD50 (Dermal)4350 mg/kg Rabbit

LC50 (Inhalation)26 mg/l/4h Rat

DIPHENYLMETHANE-4,4'-DIISOCYANATE

LD50 (Oral)> 2000 mg/kg

LD50 (Dermal)> 9400 mg/kg

LC50 (Inhalation)1,5 mg/l/4h

DIPHENYLMETHANE-4,4'-DIISOCYANATE

LD50 (Oral)> 5000 mg/kg rat

LD50 (Dermal)> 9400 mg/l rabbit; OECD TG 402

LC50 (Inhalation)1,5 mg/l/4h rat; OECD TG 403

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

DIPHENYLMETHANE-4,4'- DIISOCYANATE

LC50 - for Fish > 1000 mg/l/96h

EC50 - for Crustacea > 1000 mg/l/48h

EC10 for Algae / Aquatic > 1640 mg/l/72h

Plants

DIPHENYLMETHANE-4,4'- DIISOCYANATE

LC50 - for Fish > 100 mg/l/96h Brachydanio Rerio; OECD TG 203

EC50 - for Crustacea 83 mg/l/48h Daphnia Magna; OECD TG 202

EC50 - for Algae / Aquatic > 100 mg/l/72h Desmodesmus subspicatus; OECD TG 201

Plants

12.2. Persistence and degradability

PHOSPHORIC ACID

Solubility in water > 850000 mg/l

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 13
Dated 07/07/2016
Printed on 29/08/17
Page n. 12/17

30564 - GELFLEX 333 NERO

Degradability: information not available

XYLENE (MIXTURE OF ISOMERS)

Solubility in water mg/l 100 - 1000

Degradability: information not available

DIPHENYLMETHANE-4,4'-DIISOCYANATE

Solubility in water mg/l 0,1 - 100

NOT rapidly degradable

DIPHENYLMETHANE-4,4'-DIISOCYANATE

NOT rapidly degradable

ETHYL ACETATE

Solubility in water > 10000 mg/l

Rapidly degradable

12.3. Bioaccumulative potential

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: n-octanol/water 3,12

BCF 25,9

DIPHENYLMETHANE-4,4'-DIISOCYANATE

Partition coefficient: n-octanol/water 4,51

BCF 200

DIPHENYLMETHANE-4,4'-DIISOCYANATE

BCF < 14

ETHYL ACETATE

Partition coefficient: n-octanol/water 0,68

BCF 30

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@inet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 13
Dated 07/07/2016
Printed on 29/08/17
Page n. 13/17

30564 - GELFLEX 333 NERO

12.4. Mobility in soil

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: 2,73
soil/water

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@inet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 13
Dated 07/07/2016
Printed on 29/08/17
Page n. 14/17

30564 - GELFLEX 333 NERO

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso category None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3

Contained substance

Point 56 DIPHENYLMETHAN
E-4,4'-
DIISOCYANATE

Point 56 DIPHENYLMETHAN
E-4,4'-
DIISOCYANATE
Reg. no.: 01-
2119457014-47

Substances in Candidate List (Art. 59 REACH)

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 13
Dated 07/07/2016
Printed on 29/08/17
Page n. 15/17

30564 - GELFLEX 333 NERO

None

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) :

Special finishes.

VOC given in g/litre of product in a ready-to-use condition :

Limit value: 840,00

VOC of product : 121,92

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Carc. 2	Carcinogenicity, category 2
Acute Tox. 4	Acute toxicity, category 4
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1B	Skin corrosion, category 1B

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414

Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 13
Dated 07/07/2016
Printed on 29/08/17
Page n. 16/17

30564 - GELFLEX 333 NERO

Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Resp. Sens. 1	Respiratory sensitization, category 1
Skin Sens. 1	Skin sensitization, category 1
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H351	Suspected of causing cancer.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH204	Contains isocyanates. May produce an allergic reaction.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labelling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation

236 Maddington Road Maddington 6109
Western Australia
Ph: 08 9493 7948 Fax: 08 9493 2414
Email: ozgel@iinet.net.au
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL
ABN: 38 926 088 116



Revision nr. 13
Dated 07/07/2016
Printed on 29/08/17
Page n. 17/17

30564 - GELFLEX 333 NERO

- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

02 / 03 / 08 / 09 / 10 / 11 / 12 / 15 / 16.