

236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 9  
Dated 11/09/2015  
Printed on 08/08/2017  
Page n. 1/14

**45320-45321-45322-45323 - POLISH T57 DARK**

## Safety data sheet

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: 45320-45321-45322-45323  
Product name: POLISH T57 DARK

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Polish compound

#### 1.3. Details of the supplier of the safety data sheet

Name: GELSON SRL  
Full address: Via Varese 11/13  
District and Country: 20020 Lainate (MI) Italia  
Tel. +39 02 9370640  
Fax +39 02 93797341

e-mail address of the competent person responsible for the Safety Data Sheet: info@gelson.it

Australian distributor: OZ-GEL  
236 Maddington Rd  
Maddington 6109 Western Australia  
ozgel@iinet.net.au

Australian distributor phone number: 0418 913 426 (general information)  
Local Distributor:

#### 1.4. Emergency telephone number

For urgent inquiries refer to: POISONS INFORMATION CENTRE  
Australia Tel. 13 11 26  
New Zealand Tel. 0800 764 766

### SECTION 2. Hazards identification.

#### 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3 H226 Flammable liquid and vapour.

#### 2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 9  
Dated 11/09/2015  
Printed on 08/08/2017  
Page n. 2/14

## 45320-45321-45322-45323 - POLISH T57 DARK



Signal words: Warning

### Hazard statements:

**H226** Flammable liquid and vapour.  
**EUH066** Repeated exposure may cause skin dryness or cracking.

### Precautionary statements:

**P210** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
**P233** Keep container tightly closed.  
**P280** Wear protective gloves / eye protection / face protection.  
**P303+P361+P353** IF ON SKIN (or hair): take off immediately all contaminated clothing. Rinse skin with water / shower.  
**P370+P378** In case of fire: use CO2 or powder to extinguish.

### 2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

## SECTION 3. Composition/information on ingredients.

### 3.1. Substances.

Information not relevant.

### 3.2. Mixtures.

Contains:

| Identification.   | Conc. %. | Classification 1272/2008 (CLP).  |
|---|----------|--|
| <b>Idrocarburi C11-C13 isoalcani &lt;2% aromatici</b><br>CAS. 90622-58-5<br>EC. 920-901-0<br>INDEX. -<br>Reg. no. 01-2119456810-40          | 10 - 30  | Asp. Tox. 1 H304, EUH066   |
| <b>Idrocarburi C9-11 n-iso-alcani ciclici &lt;2% aromatici</b><br>CAS. 64742-48-9<br>EC. 919-857-5<br>INDEX. -<br>Reg. no. 01-2119463258-33 | 10 - 20  | Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066                            |
| <b>MORPHOLINE</b><br>CAS. 110-91-8  | 0,5 - 1  | Flam. Liq. 3 H226, Acute Tox. 3 H311, Acute Tox. 4 H302, Acute Tox. 4 H332, Skin Corr. |

236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@inet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 9  
Dated 11/09/2015  
Printed on 08/08/2017  
Page n. 3/14

## 45320-45321-45322-45323 - POLISH T57 DARK

1B H314

EC. 203-815-1

INDEX. 613-028-00-9

Reg. no. 01-2119496057-30

### Nafta (petrolio), frazioni pesanti di alchilazione

CAS. 64741-65-7

0,5 - 1

Flam. Liq. 3 H226, Asp. Tox.  
1 H304, Aquatic Chronic 4  
H413, EUH066, Note P

EC. 265-067-2

INDEX. 649-275-00-4

Reg. no. 01-2119472146-39

### 2-BUTOXYETHANOL

CAS. 111-76-2

0 - 0,5

Acute Tox. 4 H302, Acute  
Tox. 4 H312, Acute Tox. 4  
H332, Eye Irrit. 2 H319, Skin  
Irrit. 2 H315

EC. 203-905-0

INDEX. 603-014-00-0

Reg. no. 01-2119475108-36-XXXX

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## SECTION 4. First aid measures.

### 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

### 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

### 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

## SECTION 5. Firefighting measures.

### 5.1. Extinguishing media.

**236 Maddington Road Maddington 6109**  
**Western Australia**  
**Ph: 08 9493 7948 Fax: 08 9493 2414**  
**Email: ozgel@iinet.net.au**  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 9  
Dated 11/09/2015  
Printed on 08/08/2017  
Page n. 4/14

## **45320-45321-45322-45323 - POLISH T57 DARK**

### **SUITABLE EXTINGUISHING EQUIPMENT**

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

### **UNSUITABLE EXTINGUISHING EQUIPMENT**

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

### **5.2. Special hazards arising from the substance or mixture.**

#### **HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

### **5.3. Advice for firefighters.**

#### **GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### **SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## **SECTION 6. Accidental release measures.**

### **6.1. Personal precautions, protective equipment and emergency procedures.**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### **6.2. Environmental precautions.**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### **6.3. Methods and material for containment and cleaning up.**

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### **6.4. Reference to other sections.**

Any information on personal protection and disposal is given in sections 8 and 13.

## **SECTION 7. Handling and storage.**

236 Maddington Road Maddington 6109  
 Western Australia  
 Ph: 08 9493 7948 Fax: 08 9493 2414  
 Email: ozgel@iinet.net.au  
 A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
 ABN: 38 926 088 116



Revision nr. 9  
 Dated 11/09/2015  
 Printed on 08/08/2017  
 Page n. 5/14

## 45320-45321-45322-45323 - POLISH T57 DARK

### 7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s).

Information not available.

## SECTION 8. Exposure controls/personal protection.

### 8.1. Control parameters.

Regulatory References:

|     |                  |  |
|-----|------------------|--|
| AUS | Österreich       | Grenzwerteverordnung 2011 - GKV 2011   |
| BEL | Belgique         | AR du 11/3/2002. La liste est mise à jour pour 2010                                      |
| CHE | Suisse / Schweiz | Valeurs limites d'exposition aux postes de travail 2012. / Grenzwerte am Arbeitsplatz    |
| DEU | Deutschland      | MAK-und BAT-Werte-Liste 2012   |
| ESP | España           | INSHT - Límites de exposición profesional para agentes químicos en España 2015           |
| FRA | France           | JORF n°0109 du 10 mai 2012 page 8773 texte n° 102  |
| GRB | United Kingdom   | EH40/2005 Workplace exposure limits  |
| IRL | Éire             | Code of Practice Chemical Agent Regulations 2011   |
| ITA | Italia           | Decreto Legislativo 9 Aprile 2008, n.81  |
| NLD | Nederland        | Databank of the social and Economic Concil of Netherlands (SER) Values, AF 2011:18       |
| EU  | OEL EU           | Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC. |
|     | TLV-ACGIH        | ACGIH 2014   |

### Idrocarburi C11-C13 isoalcani <2% aromatici

#### Threshold Limit Value.

| Type | Country | TWA/8h |     | STEL/15min |     |
|------|---------|--------|-----|------------|-----|
|      |         | mg/m3  | ppm | mg/m3      | ppm |
| OEL  | EU      | 1200   | 171 |            |     |

### Idrocarburi C9-11 n-iso-alcani ciclici <2% aromatici

#### Health - Derived no-effect level - DNEL / DMEL

| Effects on consumers. | Effects on workers |
|-----------------------|--------------------|
|                       |                    |

**236 Maddington Road Maddington 6109**  
**Western Australia**  
**Ph: 08 9493 7948 Fax: 08 9493 2414**  
**Email: ozgel@iinet.net.au**  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 9  
Dated 11/09/2015  
Printed on 08/08/2017  
Page n. 6/14

**45320-45321-45322-45323 - POLISH T57 DARK**

| Route of exposure | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
|-------------------|-------------|----------------|---------------|------------------|-------------|----------------|---------------|------------------|
| Oral.             |             |                | VND           | 125 mg/kg        |             |                |               |                  |
| Inhalation.       |             |                | VND           | 900 mg/m3        |             |                | VND           | 871 mg/m3        |
| Skin.             |             |                | VND           | 125 mg/kg        |             |                | VND           | 208 MG/KG        |

**MORPHOLINE**

**Threshold Limit Value.**

| Type      | Country | TWA/8h |     | STEL/15min |     |       |
|-----------|---------|--------|-----|------------|-----|-------|
|           |         | mg/m3  | ppm | mg/m3      | ppm |       |
| MAK       | AUS     | 36     | 10  | 36         | 10  |       |
| VLEP      | BEL     | 36     | 10  | 72         | 20  |       |
| AGW       | DEU     | 36     | 10  | 72         | 20  | SKIN. |
| MAK       | DEU     | 36     | 10  | 72         | 20  |       |
| VLA       | ESP     | 36     | 10  | 72         | 20  |       |
| VLEP      | FRA     | 36     | 10  | 72         | 20  |       |
| WEL       | GRB     | 36     | 10  | 72         | 20  | SKIN. |
| OEL       | IRL     | 36     | 10  | 72         | 20  | SKIN. |
| TLV       | ITA     | 36     | 10  | 72         | 20  | SKIN. |
| OEL       | NLD     | 36     | 10  | 72         | 20  | SKIN. |
| OEL       | EU      | 36     | 10  | 72         | 20  |       |
| TLV-ACGIH |         | 71     | 20  |            |     | SKIN. |

**Predicted no-effect concentration - PNEC.**

|  |       |       |
|--|-------|-------|
| Normal value in fresh water                  | 0,1   | mg/l  |
| Normal value in marine water                 | 0,01  | mg/l  |
| Normal value for fresh water sediment        | 1,49  | mg/kg |
| Normal value for marine water sediment       | 0,149 | mg/kg |
| Normal value for water, intermittent release | 0,28  | mg/l  |
| Normal value of STP microorganisms           | 10    | mg/l  |
| Normal value for the terrestrial compartment | 0,239 | mg/kg |

**Health - Derived no-effect level - DNEL / DMEL**

| Route of exposure | Effects on consumers. |                |               | Effects on workers |                |               |
|-------------------|-----------------------|----------------|---------------|--------------------|----------------|---------------|
|                   | Acute local           | Acute systemic | Chronic local | Acute local        | Acute systemic | Chronic local |
| Oral.             | VND                   | 38 mg/kg       | VND           |                    |                |               |
| Inhalation.       |                       |                | VND           | 45 mg/m3           | 72 mg/m3       | VND           |
| Skin.             |                       |                | VND           | 0,52 mg/kg         |                | VND           |

**2-BUTOXYETHANOL**

**Threshold Limit Value.**

| Type | Country | TWA/8h |     | STEL/15min |     |       |
|------|---------|--------|-----|------------|-----|-------|
|      |         | mg/m3  | ppm | mg/m3      | ppm |       |
| MAK  | AUS     | 98     | 20  | 200        | 40  | SKIN. |
| VLEP | BEL     | 98     | 20  | 246        | 50  | SKIN. |
| VEL  | CHE     | 49     | 10  | 98         | 20  | SKIN. |
| MAK  | CHE     | 49     | 10  | 98         | 20  | SKIN. |
| AGW  | DEU     | 49     | 10  | 196        | 40  | SKIN. |
| MAK  | DEU     | 49     | 10  | 98         | 20  | SKIN. |
| VLA  | ESP     | 98     | 20  | 245        | 50  | SKIN. |
| VLEP | FRA     | 49     | 10  | 246        | 50  | SKIN. |
| WEL  | GRB     | 123    | 25  | 246        | 50  | SKIN. |

236 Maddington Road Maddington 6109  
 Western Australia  
 Ph: 08 9493 7948 Fax: 08 9493 2414  
 Email: ozgel@iinet.net.au  
 A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
 ABN: 38 926 088 116



Revision nr. 9  
 Dated 11/09/2015  
 Printed on 08/08/2017  
 Page n. 7/14

**45320-45321-45322-45323 - POLISH T57 DARK**

|           |     |     |    |     |    |       |
|-----------|-----|-----|----|-----|----|-------|
| OEL       | IRL | 98  | 20 | 246 | 50 | SKIN. |
| TLV       | ITA | 98  | 20 | 246 | 50 | SKIN. |
| OEL       | NLD | 100 |    | 246 |    | SKIN. |
| OEL       | EU  | 98  | 20 | 246 | 50 | SKIN. |
| TLV-ACGIH |     | 97  | 20 |     |    |       |

Predicted no-effect concentration - PNEC.

|   |         |       |
|---|---------|-------|
| Normal value in fresh water                           | 8,8     | mg/l  |
| Normal value in marine water                          | 0,88    | mg/l  |
| Normal value for fresh water sediment                 | 34,6    | mg/kg |
| Normal value for marine water sediment                | 3,46    | mg/kg |
| Normal value for water, intermittent release          | 9,1     | mg/l  |
| Normal value for the food chain (secondary poisoning) | 0,00002 | mg/kg |
| Normal value for the terrestrial compartment          | 3,13    | mg/kg |

**Health - Derived no-effect level - DNEL / DMEL**

| Route of exposure | Effects on consumers. |                |               | Effects on workers |             |                |               |                  |
|-------------------|-----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
|                   | Acute local           | Acute systemic | Chronic local | Chronic systemic   | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral.             |                       |                | VND           | 3,2 mg/kg          |             |                |               |                  |
| Inhalation.       |                       |                | VND           | 49 mg/m3           |             |                | VND           | 98 mg/m3         |
| Skin.             |                       |                | VND           | 38 mg/kg           |             |                | VND           | 75 mg/kg         |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

**8.2. Exposure controls.**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

**HAND PROTECTION**

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 9  
Dated 11/09/2015  
Printed on 08/08/2017  
Page n. 8/14

## 45320-45321-45322-45323 - POLISH T57 DARK

### ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9. Physical and chemical properties.

### 9.1. Information on basic physical and chemical properties.

|  |                                       |
|--|---------------------------------------|
| Appearance                             | pasty liquid                          |
| Colour                                 | black                                 |
| Odour                                  | aromatic                              |
| Odour threshold.                       | Not available.                        |
| pH.                                    | Not available.                        |
| Melting point / freezing point.        | Not available.                        |
| Initial boiling point.                 | Not available.                        |
| Boiling range.                         | Not available.                        |
| Flash point.                           | ≤ 55 °C.                              |
| Evaporation rate                       | Not available.                        |
| Flammability (solid, gas)              | Not available.                        |
| Lower inflammability limit.            | Not available.                        |
| Upper inflammability limit.            | Not available.                        |
| Lower explosive limit.                 | Not available.                        |
| Upper explosive limit.                 | Not available.                        |
| Vapour pressure.                       | Not available.                        |
| Vapour density                         | Not available.                        |
| Relative density.                      | 1,010 Kg/l                            |
| Solubility                             | insoluble in water                    |
| Partition coefficient: n-octanol/water | Not available.                        |
| Auto-ignition temperature.             | Not available.                        |
| Decomposition temperature.             | Not available.                        |
| Viscosity                              | > 40 sec @ 23°C (ISO 2431:1993; 6 mm) |
| Explosive properties                   | Not available.                        |
| Oxidising properties                   | Not available.                        |

### 9.2. Other information.

|                              |                           |
|------------------------------|---------------------------|
| VOC (Directive 1999/13/EC) : | 34,94 % - 352,93 g/litre. |
| VOC (volatile carbon) :      | 31,70 % - 320,18 g/litre. |

## SECTION 10. Stability and reactivity.

### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

MORPHOLINE: The product may react exothermically on contact with strong oxidizing agents or reducers, strong acids or bases.

### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions.



236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 9  
Dated 11/09/2015  
Printed on 08/08/2017  
Page n. 9/14

## 45320-45321-45322-45323 - POLISH T57 DARK

The vapours may also form explosive mixtures with the air.

### 10.4. Conditions to avoid.

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

### 10.5. Incompatible materials.

Information not available.

### 10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

## SECTION 11. Toxicological information.

### 11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product may have a degreasing action on the skin, producing dryness and chapped skin after repeated exposure.

Idrocarburi C9-11 n-iso-alcani ciclici <2% aromatici  
LD50 (Oral).> 5000 mg/kg ratto  
LD50 (Dermal).> 5000 mg/kg coniglio  
LC50 (Inhalation).> 4951 mg/m3 ratto

Idrocarburi C11-C13 isoalcani <2% aromatici  
LD50 (Oral).> 5000 mg/kg ratto  
LD50 (Dermal).> 5000 mg/kg coniglio  
LC50 (Inhalation).> 5000 mg/m3 ratto

MORPHOLINE  
LD50 (Oral).1050 mg/kg Rat  
LD50 (Dermal).500 mg/kg Rabbit  
LC50 (Inhalation).35,1 mg/l/1h Rat

2-BUTOXYETHANOL  
LD50 (Oral).615 mg/kg Rat  
LD50 (Dermal).405 mg/kg Rabbit  
LC50 (Inhalation).2,2 mg/l/4h Rat

## SECTION 12. Ecological information.

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil, sewers and waterways. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

### 12.1. Toxicity.

236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 9  
Dated 11/09/2015  
Printed on 08/08/2017  
Page n. 10/14

## 45320-45321-45322-45323 - POLISH T57 DARK

Idrocarburi C9-11 n-iso-  
alcani ciclici <2% aromatici  
LC50 - for Fish. > 1000 mg/l/96h Pesce  
EC50 - for Crustacea. 1000 mg/l/48h Daphnia Magna  
EC50 - for Algae / Aquatic  
Plants. > 1000 mg/l/72h Alga

Idrocarburi C11-C13  
isoalcani <2% aromatici  
LC50 - for Fish. 1000 mg/l/96h Fish  
EC50 - for Crustacea. 1000 mg/l/48h Crustacea  
EC50 - for Algae / Aquatic  
Plants. 1000 mg/l/72h Algae  
Chronic NOEC for  
Crustacea. 1 mg/l

MORPHOLINE  
LC50 - for Fish. 196 mg/l/96h Pesce

2-BUTOXYETHANOL  
LC50 - for Fish. 1490 mg/l/96h Lepomis macrochirus  
EC50 - for Crustacea. 1001 mg/l/48h Daphnia magna

### 12.2. Persistence and degradability.

Idrocarburi C9-11 n-iso-  
alcani ciclici <2% aromatici  
Rapidly biodegradable.

Idrocarburi C11-C13  
isoalcani <2% aromatici  
Rapidly biodegradable.

MORPHOLINE  
Solubility in water. mg/l 1000 - 10000

2-BUTOXYETHANOL  
Solubility in water. mg/l 1000 - 10000  
Rapidly biodegradable.

### 12.3. Bioaccumulative potential.

MORPHOLINE  
Partition coefficient: n-  
octanol/water. -2,55  
BCF. < 0,65

236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 9  
Dated 11/09/2015  
Printed on 08/08/2017  
Page n. 11/14

## 45320-45321-45322-45323 - POLISH T57 DARK

### 2-BUTOXYETHANOL

Partition coefficient: n-  
octanol/water. 0,81  
BCF. 2,5

### 12.4. Mobility in soil.

### MORPHOLINE

Partition coefficient:  
soil/water. -0,6196

### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### 12.6. Other adverse effects.

Information not available.

## SECTION 13. Disposal considerations.

### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

#### CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information.

### 14.1. UN number.

ADR / RID, IMDG, 1263  
IATA:

The product, if packaged in packages of less than 450 litres, is not subject to ADR regulations as stated in 2.2.3.1.5.

The product, if packaged in packages of less than 30 litres, is not subject to obligations relating to marking, labelling and package testing in accordance with 2.3.2.5 of the IMDG CODE.

### 14.2. UN proper shipping name.

ADR / RID: PAINT RELATED  
MATERIAL  
IMDG: PAINT RELATED  
MATERIAL  
IATA: PAINT RELATED  
MATERIAL

### 14.3. Transport hazard class(es).

236 Maddington Road Maddington 6109  
 Western Australia  
 Ph: 08 9493 7948 Fax: 08 9493 2414  
 Email: ozgel@iinet.net.au  
 A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
 ABN: 38 926 088 116



Revision nr. 9  
 Dated 11/09/2015  
 Printed on 08/08/2017  
 Page n. 12/14

**45320-45321-45322-45323 - POLISH T57 DARK**

ADR / RID: Class: 3 Label: 3  
 IMDG: Class: 3 Label: 3  
 IATA: Class: 3 Label: 3



**14.4. Packing group.**

ADR / RID, IMDG, IATA: III

**14.5. Environmental hazards.**

ADR / RID: NO

**14.6. Special precautions for user.**

|            |  |                         |                               |
|------------|--|-------------------------|-------------------------------|
| ADR / RID: | HIN - Kemler: 30                       | Limited Quantities 5 L  | Tunnel restriction code (D/E) |
| IMDG:      | Special Provision: -<br>EMS: F-E, S-E, | Limited Quantities 5 L  |                               |
| IATA:      | Cargo:                                 | Maximum quantity: 220 L | Packaging instructions: 366   |
|            | Pass.:                                 | Maximum quantity: 60 L  | Packaging instructions: 355   |
|            | Special Instructions:                  | A3, A72                 |                               |

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.**

Information not relevant.

**SECTION 15. Regulatory information.**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.**

Seveso category. 6

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product Point. 3 - 40

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisation (Annex XIV REACH).

236 Maddington Road Maddington 6109  
Western Australia  
Ph: 08 9493 7948 Fax: 08 9493 2414  
Email: ozgel@iinet.net.au  
A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 9  
Dated 11/09/2015  
Printed on 08/08/2017  
Page n. 13/14

## 45320-45321-45322-45323 - POLISH T57 DARK

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Information not available.

Product not intended for uses provided for by Dir. 2004/42/CE.

### 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

## SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

|                          |  |
|--------------------------|--|
| <b>Flam. Liq. 3</b>      | Flammable liquid, category 3                                       |
| <b>Acute Tox. 3</b>      | Acute toxicity, category 3   |
| <b>Acute Tox. 4</b>      | Acute toxicity, category 4   |
| <b>Asp. Tox. 1</b>       | Aspiration hazard, category 1                                      |
| <b>Skin Corr. 1B</b>     | Skin corrosion, category 1B  |
| <b>Eye Irrit. 2</b>      | Eye irritation, category 2   |
| <b>Skin Irrit. 2</b>     | Skin irritation, category 2  |
| <b>STOT SE 3</b>         | Specific target organ toxicity - single exposure, category 3       |
| <b>Aquatic Chronic 4</b> | Hazardous to the aquatic environment, chronic toxicity, category 4 |
| <b>H226</b>              | Flammable liquid and vapour.                                       |
| <b>H311</b>              | Toxic in contact with skin.  |
| <b>H302</b>              | Harmful if swallowed.  |
| <b>H312</b>              | Harmful in contact with skin.                                      |
| <b>H332</b>              | Harmful if inhaled.  |
| <b>H304</b>              | May be fatal if swallowed and enters airways.                      |
| <b>H314</b>              | Causes severe skin burns and eye damage.                           |
| <b>H319</b>              | Causes serious eye irritation.                                     |
| <b>H315</b>              | Causes skin irritation.  |
| <b>H336</b>              | May cause drowsiness or dizziness.                                 |

**236 Maddington Road Maddington 6109**  
**Western Australia**  
**Ph: 08 9493 7948 Fax: 08 9493 2414**

**Email: ozgel@iinet.net.au**

A J & A J Hubycki & Oz-Gel Imports Pty Ltd T/as OZ-GEL  
ABN: 38 926 088 116



Revision nr. 9

Dated 11/09/2015

Printed on 08/08/2017

Page n. 14/14

## **45320-45321-45322-45323 - POLISH T57 DARK**

**H413** May cause long lasting harmful effects to aquatic life.  
**EUH066** Repeated exposure may cause skin dryness or cracking.

### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labelling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

### GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
  4. Regulation (EU) 2015/830 of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - ECHA website

### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

### Changes to previous review:

The following sections were modified:

09 / 14 / 15.