

● Self adhesive Protection Film

SMASHWRAP®



Self adhesive protection film



Horn & Bauer
Folientechnik

● The advantages of **SMASHWRAP®**



● Application

- for vehicles in storage from weather prior to repair
- seal broken windows and sprung doors
- damaged sun-roofs and tailgates
- door cladding
- to protect interior of the car and foot-well areas
- to protect fender when servicing or assembling
- spray booth lining

● Material Properties

- self adhesive inside
- slippery outer surface
- strong, extremely tear resistant
- green - transparent
- easy to apply, easy to remove

● Packaging

rolls of 100 meters
width
30 cm
60 cm
90 cm

Ref.
304 759
304 760
304 761

● User guidance

- surfaces must be dry, grease and dust free
- peel back edge and unroll a small amount
- carefully press on the vehicle surface
- **unsuitable** for long term application to painted surfaces (e.g. as **transport protection for vehicles**)
Do not expose to direct sunlight, as this may cause damage to the paint surface.
- Self adhesive film should not be stored at temperatures over + 65 °C or below -10 °C
This can lead to glue residues.
- best to be used between +5 °C and +30 °C
- due to a wide variety of possible applications, the user must test the suitability of the film for each application.

● Storage

roll should be stored dry and not in direct sun light

● www.better-protection.com

for more features and videos of application
ask for our CD-ROM or visit above website