



1890 Rapid Cut

GELSON®AZIENDA CON SISTEMA QUALITÀ
CERTIFICATO DA DNV
UNI EN ISO 9001

Pag. 1/1

TECHNICAL DATA SHEET

Rev. 3 del 19/02/2009

Liquid rubbing compound for polishing of polyurethane clearcoats (cars, trucks, boats) and other automotive paints.

1890 can be used as a single-step coarse/finishing rubbing compound; it doesn't leave holograms or scratches.

1890 is a silicon-free product.

CHARACTERISTICS:

Form: Creamy liquid
Colour: Black/gray
Base: Water emulsion O/W
Density : 1,13 g/cm³

USE:

Machine (polisher) use.
Merinos wool pads are used to remove sending scratches or scratches from car-wash.
Finishing: Angle foam pad, green or black.
Residues' removal and final polishing should be made using an Orange Microfiber cloth.
Eventual application of polish (Polish T98 Long Life – Polish Dark T98) would just improve paint protection.



STORAGE:

12 months in its original unopened container.
Store frost free!

PACKAGING:

Code	Colour	Packaging
40440	Gray	1 litre
40460	Black	1 litre

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.