



1898 Super Rapid Cut

GELSON®AZIENDA CON SISTEMA QUALITÀ
CERTIFICATO DA DNV
UNI EN ISO 9001

Pag. 1/1

TECHNICAL DATA SHEET

Rev. 3 dated 03/04/2018

Super-coarse liquid rubbing compound for polishing of polyurethane clearcoats (cars, trucks, boats) and other automotive and marine coatings.
Silicon-free.

CHARACTERISTICS:

Form: Creamy liquid
Colour: white/black
Base: Water emulsion O/W
Density: 1,09 g/cm³

USE:

Machine use (polisher).
Apply with merinos wool pads (codes 8677...) and/or microfiber pads (codes 867TM...) / yellow hex-face pad (code 86751) / LPR polishing pads (codes 86246...A,M,V) to remove sanding scratches.
Only for dark paints, apply a second time with a white hex-face pad (code 86753) / LPR polishing pad, orange (code 86246/A) or brown (code 86246/M).
After the application, remove any residue and clean the surface using a microfiber cloth before sealing the paint with a polish.



STORAGE:

12 months in its original unopened container.
Store frost free!

PACKAGING:

| Code | Colour | Packaging |
|---------|--------|-----------|
| 40470 | white | 1 litre |
| 40470/5 | white | 5 litres |
| 40475 | black | 1 litre |
| 40475/5 | black | 5 litres |

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.