



# MASTICE 34 MP

**GELSON®**AZIENDA CON SISTEMA QUALITÀ  
CERTIFICATO DA DNV  
UNI EN ISO 9001

Page 1/1

## PRODUCT DATA SHEET

Rev. 2 dated 13/10/2009

Black polybutyl-based sealing gum.  
Outstanding moisture resistance, good water resistance.  
Odorless, does not cure.

Applications:

- sealing gaps between gaskets and painted metal sheets or windows
- sealing chassis and car body
- sealing between metal sheets

Not suitable for filling cavities.

Application temperature: +5°C to +30°C

### CHARACTERISTICS:

Appearance: paste  
Base: polybutene  
Density : 1.7 g/cm<sup>3</sup>  
Colour: black  
Temperature resistance: -30°C to +70°C  
Change of volume: around 8%

### INSTRUCTIONS FOR USE:

Thoroughly clean, dry and degrease the surfaces to be treated.  
Extrude the sealant into the cracks successively removing the excess quantity.  
Extrudable with both manual and automatic guns.

### STORAGE:



The product can be stored, in its original packaging, for 12 months in a cool, dry place.

### AVAILABLE PACKAGINGS:

Code	Colour	Packaging
30408	black	Cartridges of 310 ml

*The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.*