



ABRAPLEX

GELSON®

AZIENDA CON SISTEMA QUALITÀ
CERTIFICATO DA DNV
UNI EN ISO 9001

Page 1/1

DATA SHEET

Rev. 1 dated 18/09/2007

Liquid abrasive paste expressly designed to **treat Plexiglas or polycarbonate surfaces**, such as speedboat and aircraft windscreens, portholes, etc.

Polishing Plexiglas surfaces is particularly difficult as it is a delicate material and most polishing products available on the market are either too aggressive or are ineffective. A polishing cycle has been created using Abraplex offering an effective solution to the problem in a few simple steps.

CHARACTERISTICS:

Appearance: white, creamy liquid

Base: aqueous emulsion

Density: 1.14 g/cm³

POLISHING CYCLE:

- Removal of surface marks by **wet** sanding using a **green BUFLEX** disk, grain P2500 – Ø75 mm (Velcro support).

N.B. : to remove deep marks, first sand with a **TOLEX** disk, grain P2000, Ø75 mm.

- Finish removing any surface marks and even out the surface by **wet** sanding using a **grey BUFLEX** disk, grain P3000 – Ø75 mm (Velcro support).
- Polish the surface using **ABRAPLEX** liquid abrasive paste and a foam medium pad.
- Finish with Polish T47 using a soft foam pad.



STORAGE:

If kept in its original package the product can be stored for 12 months.
Keep away from frost!

PACKAGE SIZES AVAILABLE:

Code	Colour	Package size
40280		1 litre

The effectiveness of our products is based on practical experience and research carried out in our laboratory. However, we decline any responsibility for work carried out, as it is evident that the result can be strongly influenced by a series of factors beyond our control.