



Clearcoat BLENDER

GELSON®AZIENDA CON SISTEMA QUALITÀ
CERTIFICATO DA DNV
UNI EN ISO 9001


Page 1/2

TECHNICAL DATA SHEET

Rev. 0 dated 18/10/2017

BLENDER is designed for spot repair and blending of clearcoats. Its smoothing and evening effect eliminates any visual difference between new and old applications. It can be used with any 2-component clearcoat.

MIXING RATIO:



Ready to use. The product is also available as an aerosol can. Shake well before use.

APPLICATION:

**With spray gun:**

Apply 1-2 thin coats immediately after applying the last layer of clearcoat. Use with HVLP gun, nozzle Ø 1.2 mm, or with THE gun, nozzle Ø 1.3 mm.

With aerosol can:


Apply 2-3 even coats.

POLISHING



After the clearcoat has thoroughly dried (see related technical documentation), if needed, the surface can be polished with extra-fine rubbing compound or abrasive polish.

STORAGE



12 months in the original packaging. Keep away from frost!

AVAILABLE PACKAGING:

Code

157CCB/1

25157CCB/400

Packaging

1 L

Spray 400 mL

The effectiveness of our products is based on practical experience and research carried out in our laboratory. However, we decline any responsibility for work carried out, as it is evident that the result can be strongly influenced by a series of factors beyond our control.