



CAR PROTECTOR

GELSON®

AZIENDA CON SISTEMA QUALITÀ
CERTIFICATO DA DNV
UNI EN ISO 9001

Pag. 1/1

PROVISIONAL PRODUCT DATA SHEET

Rev. 1 dated 17/06/2019

Temporary coating for metals and coated surfaces. The clear protective layer does not affect substrate appearance and gloss.

It has been especially formulated for the protection of vehicles stocked outdoor: it resists the effects of rain, UV-rays and bird droppings.

The formulation does not contain any solvent that could attack coating or plastic and rubber parts.

Can be easily removed with remover DWX190 for water-based waxes or with alkaline water solution.

CHARACTERISTICS:

Base: acrylic polymer in hydro-alcoholic solution.

Color: clear - yellowish

Specific gravity: $0.86 \text{ g/cm}^3 \pm 0.06$

pH: 7.4 ± 0.4



APPLICATION:

The product is ready to use and should not be thinned.

Apply with spray gun.

Recommended film thickness:


wet film: 40 - 60 μm

dry film: 6 - 10 μm

Dust-dry: 10-20 minutes

The product can be easily removed with DWX190 (code 20190), added to water in ratio 1:3 to 1:4, or with an alkaline water-based dewaxing solution.

Spray with mixed-air or airless systems, both handheld and automatized.



STORAGE:

12 months, in original unopened container. Store in a cool, dry place.

Please find available codes and packaging for this product on our corporate website
<http://www.gelson.it>



For this product, video resources are available on our Youtube channel. Use your smartphone to scan the QR-code on the right or follow the link:

<https://www.youtube.com/channel/UCDDaUf6YkgFeAZ69nRC1Evw>



The effectiveness of our products is based on practical experience and research carried out in our laboratory. However, we decline any responsibility for work carried out, as it is evident that the result can be strongly influenced by a series of factors beyond our control.