



GEL CABIN

STICKY COATING FOR SPRAY CABINS

GELSON®AZIENDA CON SISTEMA QUALITÀ
CERTIFICATO DA DNV
UNI EN ISO 9001

Page 1/1

TECHNICAL DATA SHEET

Rev. 3 dated 01/10/2015


Gel-Cabin is a water based transparent liquid with sticky properties, which is applied in a thin layer in spray cabins., where it collects and retains dust particles.

It can be applied onto walls, ceilings, lights and ventiducts in spray cabins.

Once the watery part has dried, the resulting clear and transparent surface will keep its sticky properties for a long time, capturing paint overspray, dust and other small particles during the painting.


CHARACTERISTICS:

Base: aqueous solution
Specific gravity : 1,04 g/cm³ ± 0,03
pH: 6,4/7,0
Colour: transparent clear / light yellow
Usage: 1 liter per 10/15 m²
Solubility: water



APPLICATION:

The surface to be treated must be clean, dry and degreased.
Gel Cabin is ready to use and can be applied by brush, by roll or with a spray gun (press.2 - 3 atm.)
It should removed and reapplied every 2/3 months, or more often if saturated by a frequent use of the spray cabin. It can be easily removed by hot water or using a steam jet cleaner.
Gel Cabin is bio-degradable



STORAGE:

12 months, in its original package and in a cool, dry place
Keep away from frost!

PACKAGING AVAILABLE:

Code No.	Colour	Package
58301		1 L
58302		120 L
58303		25 L

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.