



# GEL-MASK

Waterbased strippable coating

**GELSON®**

AZIENDA CON SISTEMA QUALITÀ  
CERTIFICATO DA DNV  
UNI EN ISO 9001

Pag. 1/1

## TECHNICAL DATA SHEET

Rev. 1 dated 11/09/2009

GEL-MASK is a temporary protective coating against dust, paint overspray etc. It is suitable for protecting car and vans bodies, motor housing, underwheels, spray booths walls, fans, scale dishes or working surfaces. Not aggressive on surfaces. The coating film can be removed with water.

### CHARACTERISTICS:

Appearance: clear green liquid  
Specific gravity:  $0.89 \text{ g/cm}^3 \pm 0.02$

### APPLICATION:

Ready to use. Can be applied by brush or with gravity feed spray gun (nozzle  $\varnothing$  1.8 -2.2 mm). Drying time: about 1 hour (23°C 50% r.h.).

### STORAGE:



12 months, in the original package, in a cool, dry place (+5°C up to +25°C).

### AVAILABLE PACKAGINGS:

Code	Colour	Package
58211	Green	5 litres

*The effectiveness of our products is based on practical experience and research carried out in our laboratory. However, we decline any responsibility for work carried out, as it is evident that the result can be strongly influenced by a series of factors beyond our control.*