

# **LC 200**



=UNI EN ISO 9001=

Page 1/1

## TECHNICAL DATA SHEET

Rev. 2 dated 07/10/2009

LC20 is a water-based cleaning, lubricating and polishing liquid.

It is an optimum cleaner agent for all painted surfaces, designed to remove impurities, soot and layers degraded by the action of UV rays with Abrasive Rubber Blocks KS8000.

#### **CHARACTERISTICS**

Base: aqueous solution

Specific gravity: 1 g/cm<sup>3</sup> ± 0.02

Colour: green APPLICATION:

Ready to use.

Painted and reinforced plastic surfaces: apply LC200 on the surface to be treated using the standard sprayer and clean with a cloth (HITEX 4000). KS8000 Abrasive Rubber Block: apply abundantly on the surface with the standard sprayer in order to reduce the friction of the abrasive block on the surface to be treated. Use a soft cloth to dry (HITEX 4000) and remove the impurities separated by KS8000.



### STORAGE:

12 months in a cool, dry place

#### **AVAILABLE PACKAGINGS:**

Code	Colour	Package
45050	Green	5 litres + sprayer

The effectiveness of our products is based on practical experience and research carried out in our laboratory. However, we decline any responsibility for work carried out, as it is evident that the result can be strongly influenced by a series of factors beyond our control.