

## M55

One-component nitrocellulosic quick filler paste. Very suitable for spot repair and for filling small imperfections such as scratches and pinholes.

Easy to apply, dries quickly in thin layers. Minimal shrinkage, good flexibility.

It can be applied on polyester putties, acrylic primers, steel, aluminum, and zinc-coated surfaces.

### CHARACTERISTICS

- Base: nitrocellulosic resins
- Specific gravity:  $1,71 \text{ g/cm}^3 \pm 0,05$
- Colour: light grey
- Appearance: smooth, fine grain.
- Low thixotropy
- Excellent ease of sanding

### APPLICATION

Can be easily applied by knife directly to:

- Polyester putty
- Acrylic primer
- Metal: steel, aluminum, and zinc-coated surfaces

Clean, degrease, dry and matt surface prior to application.

Apply the product in thin layers and let it dry for 15-30 minutes between coats.

The total film thickness should not exceed 70-80 microns.

Do not apply below 5°C.

### MINIMUM SANDING TIME

By air at 20°C: 30-50 minutes depending on layer thickness.

### SANDING

Dry sanding by hand or machine.

Sequence: P240 – P400

*The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.*

\* For any information about product codes or packs, please see our catalogue, our price list or contact us.