



PARAFFINA LIQUIDA

GELSON[®]AZIENDA CON SISTEMA QUALITÀ
CERTIFICATO DA DNV
UNI EN ISO 9001

Page 1/1

TECHNICAL DATA SHEET

Rev. 1 dated 04/09/2009

Paraffin dispersion in styrene monomer and solvent.

It can be used on gel-coat, resins and coatings for enhancing superficial curing.

CHARACTERISTICS:

Base: paraffin solution in styrene and solvent

Dry residue: 5 ± 1 %

Appearance: clear liquid

DOSE OF USE:

2% - higher percentages can result in yellowing phenomena.

Before applying the product, make sure that it is perfectly clear. In case of opalescence or crystallization, heat it in a water bath with water temperature not exceeding 40°C and wait until it has cooled to room temperature again before applying.



STORAGE:

3 months, in a cool, dry area in its original package.

Excessively low storage temperature can result in product crystallization. In this case, it is sufficient to heat the product and slowly shake it.

PACKAGING AVAILABLE:

Code	Colour	Package
MS65289		100 mL
MS65288		360 mL
MS65286		5 Kg

The effectiveness of our products is based on practical experience and research carried out in our laboratory. However, we decline any responsibility for work carried out, as it is evident that the result can be strongly influenced by a series of factors beyond our control.