



FLATTING COMPOUND FINE GREEN FLATTING COMPOUND

GELSON®AZIENDA CON SISTEMA QUALITÀ
CERTIFICATO DA DNV
UNI EN ISO 9001

Page 1/1

TECHNICAL SHEET

Rev. 2 dated 07/10/2009

These products are used for repairs and touch-ups of panels to even the old part with the new one without making a clean cut.

In case of double-layer coatings, or other pastel-colored enamels, they ensure a better adhesion between the old and the new paint.

These compounds eliminate the danger of deep signs, which usually become evident only when the work is completed and the product has dried, thus compromising the final result. Moreover, there is no danger of "peeling" already painted corners.

Both products are water-based and leave surfaces clean, residue-free and ready for painting.

CHARACTERISTICS:

Appearance: aqueous dispersion of synthetic abrasives
Specific gravity 1,44 g/cm³ (40250) – 1,33 g/cm³ (40260)
Colour: beige (40250), green (40260)

APPLICATION:

Use as a support abrasive steel wool K9006950, moist and well drained.
Apply an adequate amount of compound, then rub by hand applying a moderate pressure on the part that has to be flattened to obtain a matt, homogeneous surface.

Dry and remove any old residue until the part is ready for painting.

STORAGE:



12 months in a cool and dry place.
Keep away from frost!

AVAILABLE PACKAGINGS:

Code	Colour	Package
40250	Beige	Tube 250 ml
40260	(Fine) green	1 litre

The efficiency of our products is based on the practical experience and research carried out in our laboratories. Nonetheless, we will not be held responsible for works carried out according to our instructions since it is obvious that the final result still depends on various unpredictable factors.