

## PRIMER PER PLASTICHE

### DESCRIPTION

Clear single-component adhesion promoter for plastic and rubber in general. It is ideal for bumpers and side strips of cars and motorbikes. Excellent anchoring to treated surfaces. It does not drip and gives excellent results with a single application.

### TYPICAL FEATURES

Base: solution of adhesion promoters/resins in solvent

Density: 0.9 g/cm<sup>3</sup>

Appearance: transparent liquid

Dry film thickness: 1-4 microns

Theoretical coverage: 0.5-1 m<sup>2</sup>/can at 1 micron of dry film

### APPLICATION

Completely eliminate any previous sealant, silicone, oil, dust...

Shake the canister well before use.

If necessary, apply masking tape on all sides of the part to be protected.

Sand finely with a hand pad (Kofle-x). After thorough cleaning, apply two light coats of the product. The substrate may be painted over only for a short time (6-12 hours).

If you wait too long a new application will be necessary.

After use, turn the can upside down and spray for 2-3 seconds to clean the nozzle and have the can ready for subsequent uses.

### PAINTING OVER

Let the primer dry for at least 20 minutes at 20°C before covering it. The primer can be coated within 6-12 hours with all single-component and two-component fillers, basecoats and topcoats.

*L'efficacia dei nostri prodotti è basata su esperienze pratiche e ricerche effettuate nei nostri laboratori. Tuttavia, decliniamo ogni responsabilità per i lavori effettuati, essendo evidente che il risultato è fortemente condizionato da una serie di fattori al di fuori del nostro controllo.*

\* Per informazioni su codici e confezioni disponibili per questo prodotto consultate il nostro catalogo, il nostro listino o contattateci

**GELSON S.r.l.**

Lainate (Milan) 20045 Italy - Via Varese 11/13  
 TEL +39 029370640  
 FAX +39 0293570880  
 MAIL info@gelson.it

