



REV.4 07/03/2024

#### PRIMER PER POLIPROPILENE

#### **DESCRIPTION**

High performance one-component adhesion promoter. Specially formulated to solve the adhesion problems of polyolefin plastics (PP, PE, TPO, EPDM), commonly used for car bumpers.

Double function: it can be used as an adhesion promoter both for coating and for two-component adhesives such as Gel-mix and Plio-Gel.

The product is also available in aerosol version.

# **TYPICAL FEATURES**

Base: solution of adhesion promoters/resins in solvent

Density: 0.9 g/cm<sup>3</sup>

Appearance: transparent liquid

Dry residue : about 8% Dry film thickness: 3-5 microns

Theoretical coverage: 15-20 m<sup>2</sup>/L at 5 microns of dry film

## SUBSTRATE PREPARATION

Clean and degrease thoroughly the substrate with a water-based detergent, then dry carefully.

#### **APPLICATION**

Spray gun; nozzle  $\emptyset$  1.3 – 1.4 mm, pressure 3 -4 atm. Apply 2 coats waiting 5 to 10 minutes between them. Recommended thickness 3-5 micron (up to 10 microns).

#### **PAINTING OVER**

Can be painted over with all acrylic and polyurethane fillers, basecoats and topcoats.

Wet on wet with solvent-based coatings; after drying with water-based basecoats.

If the product has fully hardened (more than 24 hours after application), sand lightly and apply a fresh coat before painting over.

## **REPAIR WITH STRUCTURAL ADHESIVES**

If used as an adhesion promoter for two-component polyurethane adhesives, the spray package is recommended for ease of use.

Let the product dry for at least 15-20 minutes and no more than 12 hours before proceeding with applying the adhesive.

L'efficacia dei nostri prodotti è basata su esperienze pratiche e ricerche effettuate nei nostri laboratori. Tuttavia, decliniamo ogni responsabilità per i lavori effettuati, essendo evidente che il risultato è fortemente condizionato da una serie di fattori al di fuori del nostro controllo.



<sup>\*</sup> Per informazioni su codici e confezioni disponibili per questo prodotto consultate il nostro catalogo, il nostro listino o contattateci