



PS57 PAINT SEALER

GELSON®

AZIENDA CON SISTEMA QUALITÀ
CERTIFICATO DA DNV
UNI EN ISO 9001

Page 1/1

TECHNICAL DATA SHEET

Rev. 0 dated 16/05/2019

Paint sealing polish. Gives outstanding color depth. Protects mouldings and textured plastic parts and does not turn white over time.

CHARACTERISTICS

Base: O/W emulsion
Specific gravity: 0.94 g/cm³ ± 0.05
Colour: cream


APPLICATION:

Shake well before use.

Apply only on clean and dry surfaces. Do not apply on hot surfaces.

By hand: apply a small amount of product on a handheld pad (code no. 86340/115N) or an orange microfiber soft cloth (code no. 48370). Remove the residues and wipe with a clean, soft cloth (gold microfibre cloth – code no. 48340).

By machine, with roto random orbit polisher: apply a small amount of product with a soft LPR pad (code no. 86246/...R); remove the residues and wipe with a clean, soft cloth (gold microfibre cloth – code no. 48340) or grey polishing bonnet.



STORAGE:

12 months between 10 and 30°C, in original, unopened container.
Keep away from frost!

Please find available codes and packaging for this product on our corporate website

<http://www.gelson.it/>



For this product, video resources are available on our Youtube channel. Use your smartphone to scan the QR-code on the right or follow the link:
<https://www.youtube.com/channel/UCDDaUf6YkgFeAZ69nRC1Evv>



The effectiveness of our products is based on practical experience and research carried out in our laboratory. However, we decline any responsibility for work carried out, as it is evident that the result can be strongly influenced by a series of factors beyond our control.