



# REMOVER RC 616

**GELSON®**

AZIENDA CON SISTEMA QUALITÀ  
CERTIFICATO DA DNV  
UNI EN ISO 9001

Page 1/1

## TECHNICAL DATA SHEET

Rev.0 dated 07/06/2016

Industrial solvent for treatment and cleaning of metal and plastic surfaces. It removes glues and rubber adhesives from car plastic parts without damaging the surface.

### CHARACTERISTICS:

Composition: solvents and surfactants mixture  
Specific gravity: 0.9 kg/l  
Emulsionable in water




### APPLICATION:

SPRAY the undiluted product on the surface. After waiting a few minutes, scrub with a brush and rinse thoroughly.

Alternatively, SOAK the items to be cleaned in the undiluted product as long as needed to dissolve any sticky residue. Objects can be immersed for hours, without damaging the surfaces. If necessary, scrub the residues to be removed with a brush and rinse.

When in contact with water, the product forms an emulsion that compromises its effectiveness. Do not dilute and do not store in a humid environment.



### STORAGE:

12 months in the original packaging, in a cool place.

### AVAILABLE PACKAGING

| Code    | Colour | Package  |
|---------|--------|----------|
| 80616/5 |        | 5 litres |
| 80616   |        | 1 litre  |

*The effectiveness of our products is based on practical experience and research carried out in our laboratory. However, we decline any responsibility for work carried out, as it is evident that the result can be strongly influenced by a series of factors beyond our control.*