

## SPRAY FILLER UP

### DESCRIPTION

1K high build spray primer/filler.

Its filling power makes it suitable for small repairs (Spot Repair), for filling sanding marks or irregular surfaces before applying the matt base.

It contains anti-corrosion additives and can be easily painted over with most commercially available products.

### CHARACTERISTICS:

Base: Acrylic

Specific gravity: 0,75 g/cm<sup>3</sup> ± 0,1

Colours: grey, white

Coverage: 1-1.5 m<sup>2</sup>/can

### SURFACE PREPARATION

Excellent adhesion on steel, aluminum, galvanized steel (when previously degreased and pickled), fiberglass, painted bumpers.

The surfaces to be treated must be perfectly clean, dry and degreased.

### APPLICATION

Shake the can for at least 2 minutes after you hear the mixing balls rattling inside.

Spray evenly from about 15-20 cm, 1 to 3 coats, with a 5-minutes flash-off interval.

### PAINTING OVER

At 20°C: can be overpainted after 20-30 minutes

Sanding is not required with solvent based coatings; for water based coatings or if the surface is dirty, sand it lightly with dry P400-600 sandpaper (Super Assilex Sky).

It can be easily painted over with most commercially available products.

*The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.*

\* For any information about product codes or packs, please see our catalogue, our price list or contact us.