

SPRAY FONDO ISOLANTE

DESCRIPTION

1K insulating acrylic spray primer/filler. Very suitable for small repairs (Spot Repair).
It is particularly suitable for filling sanding marks or irregular surfaces before applying the basecoat.
With easy application, quick drying, fine grain, this product gives a quick, perfect finish on small repairs.

CHARACTERISTICS:

Base: nitro-acrylic
Specific gravity: $0,80 \text{ g/cm}^3 \pm 0,3$
Colours: light grey, medium grey, dark grey
Coverage: 2-2.5 m²/can

SURFACE PREPARATION

The surfaces to be treated must be perfectly clean, dry and degreased.

APPLICATION

Shake the can for at least 2 minutes after you hear the mixing balls rattling inside.
Spray evenly from about 15-20 cm, 1 to 3 coats, with a 5-minutes flash-off interval.

PAINTING OVER

At 20°C: can be overpainted after 30-45 minutes
Sanding is not required; if the surface is dirty, sand it lightly with dry P400-600 sandpaper or wet P800-P1000 sandpaper.

Warning: Due to the technical evolution of products (especially to meet VOC regulations) and to the interaction between products in different preparation/painting cycles, test the product behavior in your cycle before using it.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.