

SPRAY GEL-FINISH

DESCRIPTION

1K anti-corrosion spray primer/finishing.

A versatile product, it offers excellent adhesion to a wide range of metal substrates. It contains zinc phosphate, which provides it with anti-rust properties.

It dries quickly, forming a fine-grained, smooth and regular surface. It can be easily overpainted with most products used in automotive applications.

CHARACTERISTICS:

Base: Poly-vinyl butyral epoxy resin

Specific gravity: $0,80 \text{ g/cm}^3 \pm 0,3$

Colours: RAL 7034, RAL 7042, RAL 7033

Coverage: 2-2.5 m²/can

SURFACE PREPARATION

Excellent adhesion on all metals of frequent use in automotive and industrial applications, for anti-corrosion cycles. Excellent adhesion also on brass, copper, aluminum and galvanized sheet metal.

The surfaces to be treated must be perfectly clean, dry and degreased.

APPLICATION

Shake the can for at least 2 minutes after you hear the mixing balls rattling inside.

Spray evenly from about 15-20 cm, 1 or 2 coats, with a 5-minutes flash-off interval.

PAINTING OVER

Extra-quick drying. Can be painted over wet-on-wet with all 1K products. If overpainting is made after more than 6 hours, sanding is necessary.

The cured film can be painted over with 2K products without sanding, even a long time after having been applied.

It is suitable for use with electrostatic painting.

At 20°C: can be overpainted after 15/20 minutes

Sanding is not required; if the surface is dirty, sand it lightly with dry P400-600 sandpaper or wet P800-P1000 sandpaper.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.