

## SPRAY NERO LUCIDO

Glossy black spray paint with acryl resin base.  
Weather and temperature resistant

### CHARACTERISTICS:

- Temperature resistance: -10°C to 100°C, with short-term peak of 120°C
- Colour: black
- Specific gravity: 0,74 g/cm<sup>3</sup> ± 0,03

### SURFACE PREPARATION

The product must be applied to a clean and degreased surface. Use a suitable degreaser and a lint-free cloth.

### APPLICATION

Shake the can for at least 20 seconds after you hear the mixing balls rattling inside.

Spray evenly from a distance of 20-30 cm using light strokes to avoid sagging.

For a better result, give two crossed coats, a few minutes after the first application.

After use, it is advisable to spray for a few seconds with the can upside down, to avoid clogging of the dispenser.

Residues can be removed with acetone.

### DRYING TIME:

Dust free: 10 minutes

Touch dry: 15 minutes

Deep dry: 1 day

*The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.*

\* For any information about product codes or packs, please see our catalogue, our price list or contact us.

## SPRAY NERO OPACO

Matt black spray paint with acryl resin base.  
Weather and temperature resistant

### CHARACTERISTICS:

- Temperature resistance: -10°C to 100°C, with short-term peak of 120°C
- Colour: black
- Specific gravity: 0,74 g/cm<sup>3</sup> ± 0,03

### SURFACE PREPARATION

The product must be applied to a clean and degreased surface. Use a suitable degreaser and a lint-free cloth.

### APPLICATION

Shake the can for at least 20 seconds after you hear the mixing balls rattling inside.

Spray evenly from a distance of 20-30 cm using light strokes to avoid sagging.

For a better result, give two crossed coats, a few minutes after the first application.

After use, it is advisable to spray for a few seconds with the can upside down, to avoid clogging of the dispenser.

Residues can be removed with acetone.

### DRYING TIME:

Dust free: 10 minutes

Touch dry: 15 minutes

Deep dry: 1 day

*The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.*

\* For any information about product codes or packs, please see our catalogue, our price list or contact us.

## SPRAY ALLUMINIO RUOTE

Metallic gray spray paint with acryl resin base.  
Weather and temperature resistant

### CHARACTERISTICS:

- Temperature resistance: -10°C to 100°C, with short-term peak of 120°C
- Colour: metallic (aluminum)
- Specific gravity: 0,74 g/cm<sup>3</sup> ± 0,03

### SURFACE PREPARATION

The product must be applied to a clean and degreased surface. Use a suitable degreaser and a lint-free cloth.

### APPLICATION

Shake the can for at least 20 seconds after you hear the mixing balls rattling inside.

Spray evenly from a distance of 20-30 cm using light strokes to avoid sagging.

For a better result, give two crossed coats, a few minutes after the first application.

After use, it is advisable to spray for a few seconds with the can upside down, to avoid clogging of the dispenser.

Residues can be removed with acetone.

### DRYING TIME:

Dust free: 10 minutes

Touch dry: 15 minutes

Deep dry: 1 day

*The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.*

\* For any information about product codes or packs, please see our catalogue, our price list or contact us.