

## SPRAY ZINC COAT

### DESCRIPTION

Cold galvanization paint based on high molecular weight synthetic resins. The product can be applied on all metal surfaces, and once cured forms a high-hardness, corrosion-resistant coating. This uniform, though metallic layer can be painted over or left as a final protection. It is ideal for retouching, for finishing and repairing of galvanized parts.

### CHARACTERISTICS

- Base: high molecular weight synthetic resins
- Specific gravity:  $0,73 \text{ g/cm}^3 \pm 0,03$
- Temperature resistance:  $300^\circ\text{C}$ , with short-term peak of  $400^\circ\text{C}$
- Colour: semi-glossy, metallic light gray

### SURFACE PREPARATION

The product must be applied to a clean and degreased surface. Use a suitable degreaser and a lint-free cloth.

### APPLICATION

Shake the can for at least 20 seconds after you hear the mixing balls rattling inside. Spray two light coats, a few minutes apart. If the dispenser becomes clogged, soak it for a few seconds in acetone.

### DRYING TIME

Dust free: 10 minutes  
Touch dry: 20 minutes  
Deep dry: 6 hours  
Overpaintable: 12 hours.

**THEORETICAL COVERAGE:** 2-3 m<sup>2</sup> per can

*The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.*

\* For any information about product codes or packs, please see our catalogue, our price list or contact us.