



STATI GEL ANTI-DUST LIQUID

GELSON®AZIENDA CON SISTEMA QUALITÀ
CERTIFICATO DA DNV
UNI EN ISO 9001

Page 1/1

TECHNICAL DATA SHEET


Rev. 2 dated 07/09/2009

Clear, water-based static liquid that attracts and retains dust. Stati-Gel can be applied on any interior where dust would cause problems. Once applied and dried, the product forms a **static** film that attracts dust and retains it on the floor.

Can be used for concrete floors or spraybooths, measurement and control rooms, computer rooms etc. Especially recommended for spraybooth floors.

CHARACTERISTICS:

Base: aqueous solution
Specific gravity: 0.98 g/cm³ ± 0,02
pH: 7.6
Appearance: clear, greenish liquid.
Consumption: 1 L for 20 m²
Water soluble.



APPLICATION:

The surface to be treated must be clean, dry and degreased.
Stati Gel is ready to use and can be applied with the appropriate applicator.
Apply evenly on the surface and let dry.
The product remains active for about a week after application. The next application does not require removal of the old layer, but the floor must be free of dust.
The product is easily removed with hot water.



STORAGE:

12 months, in its original package and in a cool, dry place
Keep away from frost!

PACKAGING AVAILABLE:

Code No.	Colour	Package
58351		25 L

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.