



# POLISH T77 DARK POLISH T67

**GELSON®**AZIENDA CON SISTEMA QUALITÀ  
CERTIFICATO DA DNV  
UNI EN ISO 9001

Pag. 1/1

## TECHNICAL DATA SHEET

Rev. 3 del 22/09/2016

Single step, slightly abrasive finishing compound. Gives high-quality finition and full depth of shade. Use Polish T67 for light colours, Polish T77 Dark for dark colours.

Designed for both fresh and old/oxidised paint.

Good resistance to weathering and to cleaning agents.

### CHARACTERISTICS:

Base: O/W emulsion

Specific Gravity: (T67) 0,95 g/cm<sup>3</sup> ± 0,02  
(T77) 0,98 g/cm<sup>3</sup> ± 0,02

Coulour: (T67) green  
(T77) black)

### APPLICATION:

Apply only on clean and dry surfaces.  
Shake well before use.

By hand: apply a small amount of product on a soft cloth (SOFTEX 5000) Hand pressure affects the polishing action. Remove the residues and rub with a clean, soft cloth (gold microfibre cloth or SOFTEX 5000 - codes 48340 and 48130).

By machine: apply a small amount of product with a soft pad (cod.86783) or an angle foam pad (cod. 86793/86792). Polisher speed: 900/1200 rpm (without pressing); remove the residues and rub with a clean, soft cloth (gold microfibre cloth or SOFTEX 5000 - codes 48340 and 48130).

For better removal of swirls, use with rotary-eccentric or rotary-orbital systems.

### STORAGE:



12 months in a cool, dry place.  
Keep away from frost!

### AVAILABLE PACKAGINGS:

Code	Product	Package
45340	POLISH T67	1 litre
45345	POLISH T77 DARK	1 litre

*The information provided in this technical sheet is prepared based on our best knowledge. However, it cannot be considered binding as a warranty since we cannot control procedures, the application site and application conditions. Therefore, we will not be held responsible for improper use of the product since the application tips indicated in this sheet are considered general by nature.*