



# POLISH T93 POLISH T95 CREAM

**GELSON®**AZIENDA CON SISTEMA QUALITÀ  
CERTIFICATO DA DNV  
UNI EN ISO 9001

Pag. 1/1

## TECHNICAL DATA SHEET

Rev. 2 dated 16/06/2017

Slightly abrasive finishing compounds.

These products quickly remove small imperfections from painted surfaces and restore paint gloss providing a quality finish.

They are specially designed to eliminate swirl marks.

**They leave no white residue on mouldings and textured plastic parts.**

Good resistance to weathering and to cleaning agents.

### CHARACTERISTICS:

Base: O/W emulsion

Specific Gravity: 0,90 g/cm<sup>3</sup> ± 0,02

Colour: cream

### APPLICATION

Apply only on clean and dry surfaces. Do not apply on hot surfaces. Do not apply in direct sun.

Shake well before use.

By hand (better with T95): apply a small amount of product on a soft cloth (SOFTEX 5000 – code 48110-48130 or ORANGE MICROFIBER CLOTH – code 48370). Hand pressure should be very light. Remove the residues and wipe with a clean, soft cloth (SOFTEX 5000 or GOLD MICROFIBER CLOTH – code 48370).

By machine (both T93 and T95): with rotary polisher, apply a small amount of product with a soft pad (code 86783 or BLACK HEX-FACE FOAM PAD – cod. 86754). Polisher speed: 900/1200 rpm (without pressing). Alternatively, use SATURN ROTO-ORBITAL POLISHER (code 859DA15) with RED LPR POLISHING PAD (code 86246).

Remove the residues and wipe with a clean, soft cloth (SOFTEX 5000 or GOLD MICROFIBER CLOTH).

### STORAGE:



12 months in a cool, dry place.

Keep away from frost!

### AVAILABLE PACKAGINGS:

Code	Product	Package
45402	T93	1 litre
45502	T95 CREAM	1 litre

*The information provided in this technical sheet is prepared based on our best knowledge. However, it cannot be considered binding as a warranty since we cannot control procedures, the application site and application conditions. Therefore, we will not be held responsible for improper use of the product since the application tips indicated in this sheet are considered general by nature.*