

ALU RIMS

Aluminium nitrocellulose paint. One-component product based on specially modified polyester resins and nitrocellulose resins, very opaque. Easy application and fast drying. Particularly suitable for renewing wheel rims.

CHARACTERISTICS

Color: aluminium

Specific gravity: 0,94 g/cm³ ± 0,05

Theoretical coverage: 7/8 m²/l after thinning

SUBSTRATE PREPARATION:

Apply only in thoroughly clean, dry and degreased surfaces.

Can be applied on:

- raw sheet metal (treated with an adhesion primer)
- Nitrocellulose and polyurethane fillers
- Different kinds of primers

APPLICATION:

Thin with 80-90% antifog nitrocellulose thinner.

Mix viscosity:

18-20 seconds (Ford 4 mm at 20°C)

Apply with a gravity-fed spray gun, nozzle Ø 1.4-1.7 mm, pressure 4-5 atm.

Apply a full coat, if necessary continue with a second coat with a flash-off time of 5 minutes between coats.

Recommended dry film thickness 30 microns.

DRYING TIMES:

Dust dry: 10-15 minutes at 20°C

Touch dry: 30-40 minutes at 20°C

Thoroughly dry: 6-8 hours at 20°C

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.