



VITRIFYING POLISH TIXI POLISH

GELSON®AZIENDA CON SISTEMA QUALITÀ
CERTIFICATO DA DNV
UNI EN ISO 9001

Page 1/1

PRODUCT DATA SHEET

Rev.2 dated 19/06/2017

Abrasive finishing compounds.

These products quickly remove small imperfections from painted surfaces operating a slightly abrasive action and restore paint gloss providing a quality finish.

They are specially designed to eliminate oxidation and swirl marks, and for cleaning and refining of the car paint.

Good resistance to weathering and to cleaning agents.

CHARACTERISTICS:

Base: O/W emulsion

Specific Gravity: 0,94 g/cm³ ± 0,02

Colour: pink

APPLICATION:

Apply only on clean and dry surfaces. Do not apply on hot surfaces. Do not apply in direct sun.

Shake well before use.


By hand: apply a small amount of product on a soft cloth (SOFTEX 5000 – code 48110-48130 or ORANGE MICROFIBER CLOTH – code 48370)

Hand pressure affects the polishing action. Remove the residues and wipe with a clean, soft cloth (SOFTEX 5000 or GOLD MICROFIBER CLOTH – code 48370).

By machine: with rotary polisher, apply a small amount of product with a soft pad (code 86783 or BLACK HEX-FACE FOAM PAD – cod. 86754). Polisher speed: 900/1200 rpm (without pressing). Alternatively, use SATURN ROTO-ORBITAL POLISHER (code 859DA15) with RED LPR POLISHING PAD (code 86246).

Remove the residues and wipe with a clean, soft cloth (SOFTEX 5000 or GOLD MICROFIBER CLOTH).

STORAGE:



12 months in a cool, dry place.

Keep away from frost!

AVAILABLE PACKAGINGS:

Code	Product	Package
45121	Vetrificante	5 litres
45122	Vetrificante	1 litre
45311	Tixi	Tube 250 ml

The information provided in this technical sheet is prepared based on our best knowledge. However, it cannot be considered binding as a warranty since we cannot control procedures, the application site and application conditions. Therefore, we will not be held responsible for improper use of the product since the application tips indicated in this sheet are considered general by nature.