



DISTACCANTE UC7

GELSON®AZIENDA CON SISTEMA QUALITÀ
CERTIFICATO DA DNV
UNI EN ISO 9001

Page 1/1

TECHNICAL DATA SHEET

Rev. 2 dated 10/09/2009

This excellent release agent can be used on metal and polyester resin molds. It is also effective on surfaces treated with polyurethane paints.

UC7 leaves the surface mirror-like and dry and does not retain any mark.

The product deposits a very tough film with very high mechanical resistance, so that the mould can be used several times after every application.

CHARACTERISTICS:

Base: releasing waxes solution in styrene

Appearance: beige, creamy

Specific gravity: $0.83 \text{ g/cm}^3 \pm 0.02$



APPLICATION:

Spread a layer of product, pressing slightly with a cotton cloth. After a few minutes, polish the surface wiping with a clean, dry cotton cloth.

Work on small surface portions, without pressing too much.

Before using the mould, check it thoroughly, wiping with a clean cotton swab to test if every part of the surface has the same degree of slipperiness. This is necessary to guarantee perfect distribution and polishing of UC7.

UC7 shows no seam between two coats.



STORAGE:

12 months in the original packaging, in a cool, dry place .

AVAILABLE PACKAGING

Code	Colour	Package
MS68401	Beige	15 Kg
MS68402	Beige	2.5 L
MS68403	Beige	500 mL

The effectiveness of our products is based on practical experience and research carried out in our laboratory. However, we decline any responsibility for work carried out, as it is evident that the result can be strongly influenced by a series of factors beyond our control.