

UNDERBODY

DESCRIPTION

One-component, protective and soundproofing coating agent based on synthetic rubber for metal sheets (side mouldings, wheel arches, trunks, doors...), plastic and GRP parts.

Primer-less application is possible on various substrates, including galvanized sheet metal.

Highlights:

- can be painted over
- excellent alkali and salt resistance
- excellent temperature resistance
- long-term anti-corrosion effect
- does not sag

Can be applied also on some plastics and PVC (check compatibility previously).

A spray-can version is available for this product.

CHARACTERISTICS:

- Base: synthetic resins
- Specific gravity: $1,12 \text{ g/cm}^3 \pm 0,03$
- Dry residue: $55 \pm 2\%$
- Colours: white, black, dark grey, light grey

SUBSTRATE PREPARATION:

Thoroughly clean and degrease the surface to be coated. Dry carefully.

APPLICATION:

Ready to use, does not need to be thinned.

Shake well before use.

Apply with the dedicated spray gun, code 85102, pressure 4-5 atm; or with spray gun code 85117 (2 atm).

OVERPAINTING:

Can be painted over with waterborne coating when completely dried and with solvent based coatings after a short flash-off.

THEORETICAL COVERAGE: 1,5-2 m²/L

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.