

## VIBRAGEL 250

### DESCRIPTION

Flexible viscoelastic sound-proofing mastic sheets used for reducing air-propagated noise and for dampening impact noise and vibrations.

### FIELD OF APPLICATION

These sheets are particularly suitable for:

- automotive sector, especially inside the doors;
- air conditioning equipment,
- household appliances, metal furniture,
- elevator cabins,
- machines and machinery of various kinds.

### COMPOSITION

- Panel: specific butyl compound;
- Upper face: acrylic self-adhesive protected by silicone paper;
- Lower face: black Kraft paper.

### CHARACTERISTICS

- Thickness: 2.3 mm
- Mass: about 4 Kg/m<sup>2</sup>

### APPLICATION

The product can be applied also at low temperatures.

The application surface must be dry, clean, free from oil, grease, dust or other impurities.

The panel surface must be in total contact with the support (avoid formation of air bubbles between the product and the support).

### STORAGE

Maximum 12 months, away from direct light, in a cool, dry place (between 5 and 40°C).

*The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.*

\* For any information about product codes or packs, please see our catalogue, our price list or contact us.