



PASTA ABRASIVA ZERO

GELSON®AZIENDA CON SISTEMA QUALITÀ
CERTIFICATO DA DNV
UNI EN ISO 9001

Pag. 1/1

TECHNICAL DATA SHEET

Rev. 1 dated 23/06/2017

Super-coarse liquid rubbing compound for polishing of polyurethane clearcoats (cars, trucks, boats) and other automotive and marine coatings.

Free of petroleum distillates, mineral oils and silicone oils.

Volatile Organic Compounds (VOC) content according to Directives 2010/75/EC and 2004/42/EC is below 0.3%.

CHARACTERISTICS:

Form: Creamy liquid
Colour: white/black
Base: Water emulsion O/W
Density: 1,09 g/cm³

USE:

Machine use (polisher).
Apply with merinos wool pads (codes 8677...) and/or microfiber pads (codes 867TM...) / yellow hex-face pad (code 86751) / LPR polishing pads (codes 86246...A,M,V) to remove sanding scratches.
Only for dark paints, apply a second time with a white hex-face pad (code 86753) / LPR polishing pad, orange (code 86246/A) or brown (code 86246/M).
After the application, remove any residue and clean the surface using a microfiber cloth before sealing the paint with a polish.



STORAGE:

12 months in its original unopened container.
Store frost free!

PACKAGING:

Code	Colour	Packaging
40000	white	1 litre
40000N	black	1 litre

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.