

ZEROPLUS PASTA ABRASIVA – RUBBING COMPOUND

Extra-coarse liquid rubbing compound 2 in 1 for polishing of polyurethane clearcoats. It quickly removes sanding marks and scratches, resulting in perfectly even, high-gloss surfaces.
Free of silicon oils.

PROPERTIES

Appearance: creamy paste
Base: Water emulsion O/W
Colour: white
Density: 1.1 g/cm³

APPLICATION PROCESS

ZEROPLUS rubbing compound can be used in different steps of the polishing process, with different pads and both rotation and random orbit polishers. It is compatible with both long and short working times.

Standard polishing of big areas (panels, full vehicle).

- First step with rotation polisher and yellow foam pad.
- Second step with random orbit polisher and OTR green pad.

Polishing of sanded surfaces:

- First step with rotation polisher and wool pad
- Second step with random orbit polisher and OTR green pad.

Removal of nibs and other small defects

- Sand with abrasive disc P1500-P2000
- Apply ZEROPLUS rubbing compound with rotation polisher and wool pad.

Wipe off with an orange or gold microfiber cloth before refinishing with a fine compound or a polish.

FOLLOWING STEPS

For better surface protection we recommend PS57 PAINT SEALER or POLISH T77/T67 or as an alternative, nanometric treatment with KIT DEFENDER or KIT SHIELD.

STORAGE

12 months in its original unopened container.
Store below 25°C.
Protect from frost.

The effectiveness of our products is based on practical experiences and research work carried out in our laboratories; nevertheless we accept no liability for work carried out following our instructions being clear that the final result depends in all cases on a series of unforeseeable factors.

* For any information about product codes or packs, please see our catalogue, our price list or contact us.