



25301 - 25302

Revision nr. 28

1942 TEXTURED SPRAY

Dated 23/11/2022

Printed on 22/06/2023

Page n. 1/26

Replaced revision:27 (Dated: 08/06/2022)

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 25301-25302
Product name: 1942 VERNICE TEXTURED (AEROSOL)
UFI: DWP0-106U-900K-C6R1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: PAINT FOR BUMPERS

1.3. Details of the supplier of the safety data sheet

Name: GELSON SRL
Full address: Via Varese 11/13
District and Country: 20045 Lainate (MI)
Italia
Tel. +39 02 9370640
Fax +39 02 93570880

e-mail address of the competent person responsible for the Safety Data Sheet

info@gelson.it

Australian distributor

Oz-Gel
236 Maddington Road
Maddington 6109 Western Australia
enquiries@ozgel.com.au
0418 913 426 (General Information)

Australian distributor phone number

1.4. Emergency telephone number

For urgent inquiries refer to

POISONS INFORMATION CENTRE
Australia Tel. 13 11 26
New Zealand Tel. 0800 764 766

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture



25301 - 25302

Revision nr. 28

1942 TEXTURED SPRAY

Dated 23/11/2022

Printed on 22/06/2023

Page n. 2/26

Replaced revision:27 (Dated: 08/06/2022)

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222	Extremely flammable aerosol.
	H229	Pressurised container: may burst if heated.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.



25301 - 25302

Revision nr. 28

1942 TEXTURED SPRAY

Dated 23/11/2022

Printed on 22/06/2023

Page n. 3/26

Replaced revision:27 (Dated: 08/06/2022)

EUH211

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary statements:

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251

Do not pierce or burn, even after use.

P410+P412

Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

P211

Do not spray on an open flame or other ignition source.

P260

Do not breathe dust / fume / gas / mist / vapours / spray.

P280

Wear protective gloves / eye protection / face protection.

Contains:

XYLENE (MIXTURE OF ISOMERS)

ACETONE

N-BUTYL ACETATE

Statements on the aspiration toxicity classification were not included in the label elements, based on section 1.3.3. of Annex I to CLP.
VOC (Directive 2004/42/EC) :

Special finishes.

VOC given in g/litre of product in a ready-to-use condition : 620,18
Limit value: 840,00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
XYLENE (MIXTURE OF ISOMERS)		
INDEX 601-022-00-9	$25,5 \leq x < 27$	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C
EC 215-535-7		STA Dermal: 1100 mg/kg, STA Inhalation mists/powders: 1,5 mg/l
CAS 1330-20-7		



25301 - 25302

Revision nr. 28

Dated 23/11/2022

Printed on 22/06/2023

Page n. 4/26

Replaced revision:27 (Dated: 08/06/2022)

1942 TEXTURED SPRAY

REACH Reg. 01-2119488216-32

PROPANE

INDEX 601-003-00-5 $19,5 \leq x < 21$ Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: U

EC 200-827-9

CAS 74-98-6

ACETONE

INDEX 606-001-00-8 $13,5 \leq x < 15$ Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

EC 200-662-2

CAS 67-64-1

REACH Reg. 01-2119471330-49

N-BUTYL ACETATE

INDEX 607-025-00-1 $10,5 \leq x < 12$ Flam. Liq. 3 H226, STOT SE 3 H336, EUH066

EC 204-658-1

CAS 123-86-4

REACH Reg. 01-2119485493-29

BUTANE

INDEX 601-004-00-0 $9 \leq x < 10,5$ Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C, U

EC 203-448-7

CAS 106-97-8

Isobutane

INDEX 601-004-00-0 $1 \leq x < 1,5$ Flam. Gas 1A H220, Classification note according to Annex VI to the CLP Regulation: C, U

EC 200-857-2

CAS 75-28-5

REACH Reg. 01-2119485395-27

TITANIUM DIOXIDE [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]

INDEX 022-006-00-2 $0,4045 \leq x < 0,4545$ Carc. 2 H351, Classification note according to Annex VI to the CLP Regulation: 10, V, W

EC 236-675-5

CAS 13463-67-7

2-METHOXY-1-METHYLETHYL ACETATE

INDEX 607-195-00-7 $0,05 \leq x < 0,1$ Flam. Liq. 3 H226, STOT SE 3 H336

EC 203-603-9

CAS 108-65-6

REACH Reg. 01-2119475791-29

QUARTZ

INDEX - $0,05 \leq x < 0,1$ STOT RE 2 H373

EC 238-878-4



25301 - 25302

Revision nr. 28

1942 TEXTURED SPRAY

Dated 23/11/2022

Printed on 22/06/2023

Page n. 5/26

Replaced revision:27 (Dated: 08/06/2022)

CAS 14808-60-7

Hydrocarbons, C9, aromatics

INDEX -

$0 \leq x < 0,05$

Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066, Classification note according to Annex VI to the CLP Regulation: P

EC 918-668-5

CAS -

REACH Reg. 01-2119455851-35

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 30,00 %

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE



25301 - 25302

Revision nr. 28

1942 TEXTURED SPRAY

Dated 23/11/2022

Printed on 22/06/2023

Page n. 6/26

Replaced revision:27 (Dated: 08/06/2022)

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

7.3. Specific end use(s)



25301 - 25302

Revision nr. 28

1942 TEXTURED SPRAY

Dated 23/11/2022

Printed on 22/06/2023

Page n. 7/26

Replaced revision:27 (Dated: 08/06/2022)

Information not available

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory References:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021

XYLENE (MIXTURE OF ISOMERS)**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
VLA	ESP	221	50	442	100	SKIN
VLEP	FRA	221	50	442	100	SKIN
VLEP	ITA	221	50	442	100	SKIN
TLV	NOR	108	25			SKIN
TGG	NLD	210		442		SKIN
VLE	PRT	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH			20			

PROPANE



25301 - 25302

Revision nr. 28

1942 TEXTURED SPRAY

Dated 23/11/2022

Printed on 22/06/2023

Page n. 8/26

Replaced revision:27 (Dated: 08/06/2022)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	1800	1000	7200	4000	
MAK	DEU	1800	1000	7200	4000	
VLA	ESP		1000			
TLV	NOR	900	500			

ACETONE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	1200	500	2400 (C)	1000 (C)	
MAK	DEU	1200	500	2400	1000	
VLA	ESP	1210	500			
VLEP	FRA	1210	500	2420	1000	
VLEP	ITA	1210	500			
TLV	NOR	295	125			
TGG	NLD	1210		2420		
VLE	PRT	1210	500			
WEL	GBR	1210	500	3620	1500	
OEL	EU	1210	500			
TLV-ACGIH			250		500	

Predicted no-effect concentration - PNEC

Normal value in fresh water	10,6	mg/l
Normal value in marine water	1,06	mg/l
Normal value for fresh water sediment	30,4	mg/kg
Normal value for marine water sediment	3,04	mg/kg
Normal value for water, intermittent release	21	mg/l
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	33,3	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	62 mg/kg/d				
Inhalation			VND	200 mg/m3	VND	2420 mg/m3	VND	1210 mg/m3
Skin			VND	62 mg/kg/d			VND	186 mg/kg/d

**25301 - 25302**

Revision nr. 28

Dated 23/11/2022

Printed on 22/06/2023

Page n. 9/26

Replaced revision:27 (Dated: 08/06/2022)

1942 TEXTURED SPRAY**N-BUTYL ACETATE****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	300	62	600 (C)	124 (C)	
VLA	ESP	241	50	724	150	
VLEP	FRA	710	150	940	200	
VLEP	ITA	241	50	723	150	
TLV	NOR		75			
TGG	NLD	150				
VLE	PRT	241	50	723	150	
WEL	GBR	724	150	966	200	
OEL	EU	241	50	723	150	
TLV-ACGIH			50		150	

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,18	mg/l
Normal value in marine water	0,01	mg/l
Normal value for fresh water sediment	0,98	mg/kg
Normal value for marine water sediment	0,09	mg/kg
Normal value for water, intermittent release	0,36	mg/l
Normal value of STP microorganisms	35,6	mg/l
Normal value for the terrestrial compartment	0,09	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation	859,7 mg/m3	859,7 mg/m3	102,34 mg/m3	102,34 mg/m3	960 mg/m3	960 mg/m3	480 mg/m3	480 mg/m3

BUTANE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	2400	1000	9600	4000	
MAK	DEU	2400	1000	9600	4000	
VLA	ESP		1000			Gases
VLEP	FRA	1900	800			
TLV	NOR	600	250			
TGG	NLD	1430				



25301 - 25302

Revision nr. 28

1942 TEXTURED SPRAY

Dated 23/11/2022

Printed on 22/06/2023

Page n. 10/26

Replaced revision:27 (Dated: 08/06/2022)

WEL	GBR	1450	600	1810	750	
WEL	GBR		4			RESP
TLV-ACGIH					1000	

TITANIUM DIOXIDE [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	10				
VLEP	FRA	10				
TLV	NOR	5				
WEL	GBR	10				INHAL
WEL	GBR	4				RESP
TLV-ACGIH		0,2				RESP

QUARTZ

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP		0,05			RESP
VLEP	FRA	0,1				RESP
VLEP	ITA	0,1				RESP
TLV	NOR	0,1				RESP
TGG	NLD	0,075				RESP
VLE	PRT	0,025				RESP
OEL	EU	0,1				RESP
TLV-ACGIH		0,025				RESP

2-METHOXY-1-METHYLETHYL ACETATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
VLA	ESP	275	50	550	100	SKIN
VLEP	FRA	275	50	550	100	SKIN



25301 - 25302

Revision nr. 28

1942 TEXTURED SPRAY

Dated 23/11/2022

Printed on 22/06/2023

Page n. 11/26

Replaced revision:27 (Dated: 08/06/2022)

VLEP	ITA	275	50	550	100	SKIN
TLV	NOR	270	50			SKIN
TGG	NLD	550				
VLE	PRT	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

Predicted no-effect concentration - PNEC	
Normal value in fresh water	0,635 mg/l
Normal value in marine water	0,0635 mg/l
Normal value for fresh water sediment	3,29 mg/kg
Normal value for marine water sediment	0,329 mg/kg
Normal value for water, intermittent release	6,35 mg/l
Normal value of STP microorganisms	100 mg/l
Normal value for the terrestrial compartment	0,29 mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				36 mg/kg bw/d				
Inhalation			33 mg/m3	33 mg/m3	550 mg/m3			275 mg/m3
Skin				320 mg/kg bw/d				796 mg/kg bw/d

Hydrocarbons, C9, aromatics					
Threshold Limit Value					
Type	Country	TWA/8h		STEL/15min	Remarks / Observations
		mg/m3	ppm	mg/m3	ppm
OEL	EU	100	19		

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	11 mg/kg				
Inhalation			VND	32 mg/m3			VND	150 mg/m3
Skin			VND	11 mg/kg			VND	25 mg/kg

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.



25301 - 25302

Revision nr. 28

Dated 23/11/2022

Printed on 22/06/2023

Page n. 12/26

Replaced revision:27 (Dated: 08/06/2022)

1942 TEXTURED SPRAY

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	aerosol	
Colour	vari colori	
Odour	solvent	
Melting point / freezing point	not available	
Initial boiling point	not applicable	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	



25301 - 25302

Revision nr. 28

1942 TEXTURED SPRAY

Dated 23/11/2022

Printed on 22/06/2023

Page n. 13/26

Replaced revision:27 (Dated: 08/06/2022)

Flash point	not applicable
Auto-ignition temperature	not available
Decomposition temperature	not available
pH	not applicable
Kinematic viscosity	not available
Solubility	soluble in organic solvents
Partition coefficient: n-octanol/water	not available
Vapour pressure	not available
Density and/or relative density	0,75
Relative vapour density	not available
Particle characteristics	not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2004/42/EC) :	82,69 % - 620,18 g/litre
VOC (volatile carbon)	69,53 % - 521,50 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

ACETONE

Decomposes under the effect of heat.

N-BUTYL ACETATE

Decomposes on contact with: water.

2-METHOXY-1-METHYLETHYL ACETATE

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.



25301 - 25302

Revision nr. 28

1942 TEXTURED SPRAY

Dated 23/11/2022

Printed on 22/06/2023

Page n. 14/26

Replaced revision:27 (Dated: 08/06/2022)

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

XYLENE (MIXTURE OF ISOMERS)

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

ACETONE

Risk of explosion on contact with: bromine trifluoride, fluorine dioxide, hydrogen peroxide, nitrosyl chloride, 2-methyl-1,3 butadiene, nitromethane, nitrosyl perchlorate. May react dangerously with: potassium tert-butoxide, alkaline hydroxides, bromine, bromoform, isoprene, sodium, sulphur dioxide, chromium trioxide, chromyl chloride, nitric acid, chloroform, peroxymonosulphuric acid, phosphoryl oxychloride, chromosulphuric acid, fluorine, strong oxidising agents, strong reducing agents. Develops flammable gas on contact with: nitrosyl perchlorate.

N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents. May react dangerously with: alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with: air.

2-METHOXY-1-METHYLETHYL ACETATE

May react violently with: oxidising substances, strong acids, alkaline metals.

10.4. Conditions to avoid

Avoid overheating.

ACETONE

Avoid exposure to: sources of heat, naked flames.

N-BUTYL ACETATE

Avoid exposure to: moisture, sources of heat, naked flames.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

ACETONE



25301 - 25302

Revision nr. 28

1942 TEXTURED SPRAY

Dated 23/11/2022

Printed on 22/06/2023

Page n. 15/26

Replaced revision:27 (Dated: 08/06/2022)

Incompatible with: acids, oxidising substances.

N-BUTYL ACETATE

Incompatible with: water, nitrates, strong oxidants, acids, alkalis, zinc.

2-METHOXY-1-METHYLETHYL ACETATE

Incompatible with: oxidising substances, strong acids, alkaline metals.

10.6. Hazardous decomposition products

ACETONE

May develop: ketenes, irritant substances.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

2-METHOXY-1-METHYLETHYL ACETATE

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

XYLENE (MIXTURE OF ISOMERS)

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

N-BUTYL ACETATE

WORKERS: inhalation; contact with the skin.



25301 - 25302

Revision nr. 28

1942 TEXTURED SPRAY

Dated 23/11/2022

Printed on 22/06/2023

Page n. 16/26

Replaced revision:27 (Dated: 08/06/2022)

2-METHOXY-1-METHYLETHYL ACETATE
WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

XYLENE (MIXTURE OF ISOMERS)

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

N-BUTYL ACETATE

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

2-METHOXY-1-METHYLETHYL ACETATE

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

Interactive effects

XYLENE (MIXTURE OF ISOMERS)

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

N-BUTYL ACETATE

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:	3,9 mg/l
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	>2000 mg/kg



25301 - 25302

Revision nr. 28

1942 TEXTURED SPRAY

Dated 23/11/2022

Printed on 22/06/2023

Page n. 17/26

Replaced revision:27 (Dated: 08/06/2022)

XYLENE (MIXTURE OF ISOMERS)

LD50 (Dermal):	4350 mg/kg Rabbit
STA (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	3523 mg/kg Rat
LC50 (Inhalation vapours):	29 mg/l/4h Rat
STA (Inhalation mists/powders):	1,5 mg/l (figure used for calculation of the acute toxicity estimate of the mixture)

ACETONE

LD50 (Dermal):	> 20 mg/kg
LD50 (Oral):	5800 mg/kg
LC50 (Inhalation vapours):	21,09 ppm/4h

N-BUTYL ACETATE

LD50 (Dermal):	> 5000 mg/kg Rabbit
LD50 (Oral):	> 6400 mg/kg Rat
LC50 (Inhalation vapours):	21,1 mg/l/4h Rat

TITANIUM DIOXIDE [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]

LD50 (Oral):	> 10000 mg/kg Rat
--------------	-------------------

2-METHOXY-1-METHYLETHYL ACETATE

LD50 (Dermal):	> 5000 mg/kg Rat
LD50 (Oral):	8530 mg/kg Rat
LC50 (Inhalation vapours):	> 23,5 mg/l/4h

Hydrocarbons, C9, aromatics

LD50 (Dermal):	> 3160 mg/kg coniglio
LD50 (Oral):	3592 mg/kg
LC50 (Inhalation vapours):	> 6193 mg/m ³ ratto

SKIN CORROSION / IRRITATION



25301 - 25302

Revision nr. 28

Dated 23/11/2022

Printed on 22/06/2023

Page n. 18/26

Replaced revision:27 (Dated: 08/06/2022)

1942 TEXTURED SPRAY

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

XYLENE (MIXTURE OF ISOMERS)

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).

The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

TITANIUM DIOXIDE [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]

The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1% or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE



25301 - 25302

Revision nr. 28

1942 TEXTURED SPRAY

Dated 23/11/2022

Printed on 22/06/2023

Page n. 19/26

Replaced revision:27 (Dated: 08/06/2022)

May cause respiratory irritation

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

Hydrocarbons, C9, aromatics

Idrocarburi, C9, aromatici: ErC50 (72h) 2,9 mg/l (Alga)
NOEC 1 mg/l (Alga).

Hydrocarbons, C9, aromatics

LC50 - for Fish	9,2 mg/l/96h Pesce
EC50 - for Crustacea	3,2 mg/l/48h Daphnia
EC50 - for Algae / Aquatic Plants	2,9 mg/l/72h

2-METHOXY-1-METHYLETHYL ACETATE

LC50 - for Fish	134 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	408 mg/l/48h Daphnia Magna

ACETONE

LC50 - for Fish	4144 mg/l/96h Pesce
EC50 - for Crustacea	1680 mg/l/48h Daphnia
EC50 - for Algae / Aquatic Plants	302 mg/l/72h Alga

12.2. Persistence and degradability



25301 - 25302

Revision nr. 28

Dated 23/11/2022

Printed on 22/06/2023

Page n. 20/26

Replaced revision:27 (Dated: 08/06/2022)

1942 TEXTURED SPRAY

Hydrocarbons, C9, aromatics
Rapidly degradable

XYLENE (MIXTURE OF ISOMERS)

100 - 1000 mg/l

Solubility in water
Rapidly degradable

TITANIUM DIOXIDE [in powder form contain
ing 1 % or more of particles with aerodynamic dia
meter $\leq 10 \mu\text{m}$]

< 0,001 mg/l

Solubility in water
Degradability: information not available

2-METHOXY-1-METHYLETHYL ACETATE

> 10000 mg/l

Solubility in water
Rapidly degradable

BUTANE

0,1 - 100 mg/l

Solubility in water
Rapidly degradable

PROPANE

0,1 - 100 mg/l

Solubility in water
Rapidly degradable

ACETONE

Rapidly degradable

N-BUTYL ACETATE

1000 - 10000 mg/l

Solubility in water
Rapidly degradable

12.3. Bioaccumulative potential

Hydrocarbons, C9, aromatics

Partition coefficient: n-octanol/water

4,5

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: n-octanol/water

3,12

BCF

25,9

2-METHOXY-1-METHYLETHYL ACETATE

Partition coefficient: n-octanol/water

1,2

BUTANE

Partition coefficient: n-octanol/water

1,09

PROPANE

Partition coefficient: n-octanol/water

1,09



25301 - 25302

Revision nr. 28

1942 TEXTURED SPRAY

Dated 23/11/2022

Printed on 22/06/2023

Page n. 21/26

Replaced revision:27 (Dated: 08/06/2022)

ACETONE

Partition coefficient: n-octanol/water -0,23
BCF 3

N-BUTYL ACETATE

Partition coefficient: n-octanol/water 2,3
BCF 15,3

12.4. Mobility in soil

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: soil/water 2,73

N-BUTYL ACETATE

Partition coefficient: soil/water < 3

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information



25301 - 25302

Revision nr. 28

Dated 23/11/2022

Printed on 22/06/2023

Page n. 22/26

Replaced revision:27 (Dated: 08/06/2022)

1942 TEXTURED SPRAY

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1950

14.2. UN proper shipping name

ADR / RID: AEROSOLS
IMDG: AEROSOLS
IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1



IMDG: Class: 2 Label: 2.1



IATA: Class: 2 Label: 2.1



14.4. Packing group

ADR / RID, IMDG, IATA: -

14.5. Environmental hazards

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
IMDG:	Special provision: - EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 150 Kg	Packaging instructions: 203
	Pass.:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Special provision:	A145, A167,	



25301 - 25302

Revision nr. 28

Dated 23/11/2022

Printed on 22/06/2023

Page n. 23/26

Replaced revision:27 (Dated: 08/06/2022)

1942 TEXTURED SPRAY

A802

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Regulated explosives precursor

The acquisition, introduction, possession or use of that regulated explosives precursor by members of the general public is subject to reporting obligations as set out in Article 9.

All suspicious transactions and significant disappearances and thefts must be reported to the relevant national contact point.

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:



25301 - 25302

Revision nr. 28

1942 TEXTURED SPRAY

Dated 23/11/2022

Printed on 22/06/2023

Page n. 24/26

Replaced revision:27 (Dated: 08/06/2022)

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) :

Special finishes.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A	Flammable gas, category 1A
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Press. Gas (Liq.)	Liquefied gas
Carc. 2	Carcinogenicity, category 2
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H351	Suspected of causing cancer.
H312	Harmful in contact with skin.



25301 - 25302

Revision nr. 28

Dated 23/11/2022

Printed on 22/06/2023

Page n. 25/26

Replaced revision:27 (Dated: 08/06/2022)

1942 TEXTURED SPRAY

H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament



25301 - 25302

Revision nr. 28

1942 TEXTURED SPRAY

Dated 23/11/2022

Printed on 22/06/2023

Page n. 26/26

Replaced revision:27 (Dated: 08/06/2022)

8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 11 / 12 / 16.