



40404 - 404045

Revision nr. 5

OXIDO IRON DECONTAMINATE

Dated 05/06/2023

Printed on 05/06/2023

Page n. 1/21

Replaced revision:4 (Dated: 05/06/2023)

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **40IR404**
Product name: **OXIDO DECONTAMINANTE PER FERODO**
UFI: **NA01-20MD-N00Y-HWEM**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **agente pulente**

1.3. Details of the supplier of the safety data sheet

Name: **GELSON SRL**
Full address: **Via Varese 11/13**
District and Country: **20045 Lainate (MI)**
Italia
Tel. **+39 02 9370640**
Fax **+39 02 93570880**

e-mail address of the competent person responsible for the Safety Data Sheet: **info@gelson.it**

Australian distributor: **Oz-Gel**
236 Maddington Road
Maddington 6109 Western Australia
enquiries@ozgel.com.au
Australian distributor phone number: **0418 913 426 (General Information)**

1.4. Emergency telephone number

For urgent inquiries refer to: **POISONS INFORMATION CENTRE**
Australia Tel. 13 11 26
New Zealand Tel. 0800 764 766

SECTION 2. Hazards identification



40404 - 404045

Revision nr. 5

Dated 05/06/2023

Printed on 05/06/2023

Page n. 2/21

Replaced revision:4 (Dated: 05/06/2023)

OXIDO IRON DECONTAMINATE

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Reproductive toxicity, category 2	H361f	Suspected of damaging fertility.
Acute toxicity, category 4	H302	Harmful if swallowed.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Serious eye damage, category 1	H318	Causes serious eye damage.
Skin irritation, category 2	H315	Causes skin irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

H361f	Suspected of damaging fertility.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.



40404 - 404045

Revision nr. 5

Dated 05/06/2023

Printed on 05/06/2023

Page n. 3/21

Replaced revision:4 (Dated: 05/06/2023)

OXIDO IRON DECONTAMINATE

Precautionary statements:

P331	Do NOT induce vomiting.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P310	Immediately call a POISON CENTER / doctor / . . .
P261	Avoid breathing dust / fume / gas / mist / vapours / spray.
P201	Obtain special instructions before use.

Contains:	Sodium thioglycolate
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
	Sulfuric acid, mono-C12-14-alkyl esters, sodium salts
	(R)-P-MENTHA-1,8-DIENE

Product not intended for uses provided for by Directive 2004/42/EC.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
INDEX -	$45 \leq x < 47,5$	Asp. Tox. 1 H304, EUH066
EC 918-481-9		
CAS -		
REACH Reg. 01-2119457273-39		
Sodium thioglycolate		
INDEX -	$15 \leq x < 16,5$	Met. Corr. 1 H290, Repr. 2 H361f, Acute Tox. 3 H301, Acute Tox. 4 H312, STOT RE 2 H373, Skin Sens. 1 H317
EC 206-696-4		LD50 Oral: 60 mg/kg, LD50 Dermal: >1000 mg/kg
CAS 367-51-1		
REACH Reg. 01-2119968564-24		



40404 - 404045

Revision nr. 5

Dated 05/06/2023

Printed on 05/06/2023

Page n. 4/21

Replaced revision:4 (Dated: 05/06/2023)

OXIDO IRON DECONTAMINATE

2-BUTOXYETHANOL

INDEX 603-014-00-0 $7 \leq x < 8$ Acute Tox. 4 H302, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC 203-905-0 LD50 Oral: 1200 mg/kg, STA Inhalation vapours: 11 mg/l
CAS 111-76-2
REACH Reg.
01-2119475108-36-XXXX

Sulfuric acid, mono-C12-14-alkyl esters, sodium salts

INDEX - $5 \leq x < 6$ Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Aquatic Chronic 3 H412
EC 287-809-4 LD50 Oral: 1800 mg/kg
CAS 85586-07-8
REACH Reg. 01-2119489463-28

(R)-P-MENTHA-1,8-DIENE

INDEX 601-096-00-2 $3,5 \leq x < 4$ Flam. Liq. 3 H226, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Skin Sens. 1B H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 3 H412
EC 227-813-5
CAS 5989-27-5
REACH Reg. 01-2119529223-47

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.
SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.
INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.
INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media



40404 - 404045

Revision nr. 5

Dated 05/06/2023

Printed on 05/06/2023

Page n. 5/21

Replaced revision:4 (Dated: 05/06/2023)

OXIDO IRON DECONTAMINATE

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.



40404 - 404045

Revision nr. 5

Dated 05/06/2023

Printed on 05/06/2023

Page n. 6/21

Replaced revision:4 (Dated: 05/06/2023)

OXIDO IRON DECONTAMINATE

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 2020:25
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
SWE	Sverige	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021

2-BUTOXYETHANOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	49	10	98 (C)	20 (C)	SKIN
MAK	DEU	49	10	98	20	SKIN Hinweis
VLA	ESP	98	20	245	50	SKIN
VLEP	FRA	49	10	246	50	SKIN
HTP	FIN	98	20	250	50	SKIN



40404 - 404045

Revision nr. 5

Dated 05/06/2023

Printed on 05/06/2023

Page n. 7/21

Replaced revision:4 (Dated: 05/06/2023)

OXIDO IRON DECONTAMINATE

VLEP	ITA	98	20	246	50	SKIN
TLV	NOR	50	10			SKIN
TGG	NLD	100		246		SKIN
VLE	PRT	98	20	246	50	SKIN
NGV/KGV	SWE	50	10	246	50	SKIN
WEL	GBR	123	25	246	50	SKIN
OEL	EU	98	20	246	50	SKIN
TLV-ACGIH		97	20			

Predicted no-effect concentration - PNEC	
Normal value in fresh water	8,8 mg/l
Normal value in marine water	0,88 mg/l
Normal value for fresh water sediment	34,6 mg/kg
Normal value for marine water sediment	3,46 mg/kg
Normal value for water, intermittent release	9,1 mg/l
Normal value for the food chain (secondary poisoning)	0,00002 mg/kg
Normal value for the terrestrial compartment	3,13 mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	3,2 mg/kg				
Inhalation			VND	49 mg/m3			VND	98 mg/m3
Skin			VND	38 mg/kg			VND	75 mg/kg

Sulfuric acid, mono-C12-14-alkyl esters, sodium salts	
Predicted no-effect concentration - PNEC	
Normal value in fresh water	0,102 mg/l
Normal value in marine water	0,01 mg/l
Normal value for fresh water sediment	3,58 mg/kg
Normal value for marine water sediment	0,358 mg/kg
Normal value for water, intermittent release	0,036 mg/l
Normal value of STP microorganisms	1084 mg/l
Normal value for the terrestrial compartment	0,654 mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				24 mg/kg bw/d				
Inhalation				85 mg/m3				285 mg/m3



40404 - 404045

Revision nr. 5

Dated 05/06/2023

Printed on 05/06/2023

Page n. 8/21

Replaced revision:4 (Dated: 05/06/2023)

OXIDO IRON DECONTAMINATE

Skin 2440 mg/kg bw/d 4060 mg/kg bw/d

(R)-P-MENTHA-1,8-DIENE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	28	5	112	20	SKIN
MAK	DEU	28	5	112	20	SKIN
VLA	ESP	168	30			SKIN
HTP	FIN	140	25	280	50	
TLV	NOR	140	25			

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,0054	mg/l
Normal value in marine water	0,00054	mg/l
Normal value for fresh water sediment	1,32	mg/kg
Normal value for marine water sediment	0,13	mg/kg
Normal value of STP microorganisms	1,8	mg/l
Normal value for the food chain (secondary poisoning)	3,33	mg/kg
Normal value for the terrestrial compartment	0,262	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	4,76 mg/kg				
Inhalation			VND	8,33 mg/m3			33,3 mg/m3	33,3 mg/m3
Skin	0,111 mg/cm2	VND			0,222 mg/cm2	VND		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.



40404 - 404045

Revision nr. 5

Dated 05/06/2023

Printed on 05/06/2023

Page n. 9/21

Replaced revision:4 (Dated: 05/06/2023)

OXIDO IRON DECONTAMINATE

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	yellowish	
Odour	pungent	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	> 60 °C	
Auto-ignition temperature	not available	



40404 - 404045

Revision nr. 5

Dated 05/06/2023

Printed on 05/06/2023

Page n. 10/21

Replaced revision:4 (Dated: 05/06/2023)

OXIDO IRON DECONTAMINATE

Decomposition temperature	not available
pH	10
Kinematic viscosity	not available
Solubility	not available
Partition coefficient: n-octanol/water	not available
Vapour pressure	not available
Density and/or relative density	0,94
Relative vapour density	not available
Particle characteristics	not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU)	57,30 % - 538,62 g/litre
VOC (volatile carbon)	48,13 % - 452,44 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

2-BUTOXYETHANOL

Decomposes under the effect of heat.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

2-BUTOXYETHANOL

May react dangerously with: aluminium, oxidising agents. Forms peroxides with: air.



40404 - 404045

Revision nr. 5

Dated 05/06/2023

Printed on 05/06/2023

Page n. 11/21

Replaced revision:4 (Dated: 05/06/2023)

OXIDO IRON DECONTAMINATE

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

2-BUTOXYETHANOL

Avoid exposure to: sources of heat, naked flames.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

2-BUTOXYETHANOL

May develop: hydrogen.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure



40404 - 404045

Revision nr. 5

Dated 05/06/2023

Printed on 05/06/2023

Page n. 12/21

Replaced revision:4 (Dated: 05/06/2023)

OXIDO IRON DECONTAMINATE

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Oral) of the mixture:	350,88 mg/kg
ATE (Dermal) of the mixture:	>2000 mg/kg

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

LD50 (Dermal):	> 5000 mg/kg Rabbit
LD50 (Oral):	> 5000 mg/kg Rat
LC50 (Inhalation vapours):	> 4,951 mg/l/4h Rat

Sodium thioglycolate

LD50 (Dermal):	> 1000 mg/kg
LD50 (Oral):	60 mg/kg
LC50 (Inhalation mists/powders):	> 2729 mg/l/4h

2-BUTOXYETHANOL

LD50 (Oral):	1200 mg/kg Guinea pig
LC50 (Inhalation vapours):	3 mg/l/4h Rat
STA (Inhalation vapours):	11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

Sulfuric acid, mono-C12-14-alkyl esters, sodium salts

LD50 (Oral):	1800 mg/kg
--------------	------------

(R)-P-MENTHA-1,8-DIENE

LD50 (Dermal):	> 5000 mg/kg Coniglio
----------------	-----------------------



40404 - 404045

Revision nr. 5

Dated 05/06/2023

Printed on 05/06/2023

Page n. 13/21

Replaced revision:4 (Dated: 05/06/2023)

OXIDO IRON DECONTAMINATE

LD50 (Oral):

4400 mg/kg Ratto

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Suspected of damaging fertility

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE



40404 - 404045

Revision nr. 5

Dated 05/06/2023

Printed on 05/06/2023

Page n. 14/21

Replaced revision:4 (Dated: 05/06/2023)

OXIDO IRON DECONTAMINATE

May cause damage to organs

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

(R)-P-MENTHA-1,8-DIENE

LC50 - for Fish	0,72 mg/l/96h
EC50 - for Crustacea	0,85 mg/l/48h
EC50 - for Algae / Aquatic Plants	0,32 mg/l/72h

2-BUTOXYETHANOL

LC50 - for Fish	1490 mg/l/96h <i>Lepomis macrochirus</i>
EC50 - for Crustacea	1001 mg/l/48h <i>Daphnia magna</i>

Sulfuric acid, mono-C12-14-alkyl esters,
sodium salts

LC50 - for Fish	3,5 mg/l/96h
EC50 - for Crustacea	4,7 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 20 mg/l/72h
Chronic NOEC for Fish	0,508 mg/l
Chronic NOEC for Algae / Aquatic Plants	0,508 mg/l

Sodium thioglycolate

LC50 - for Fish	100 mg/l/96h
EC50 - for Crustacea	38 mg/l/48h



40404 - 404045

Revision nr. 5

Dated 05/06/2023

Printed on 05/06/2023

Page n. 15/21

Replaced revision:4 (Dated: 05/06/2023)

OXIDO IRON DECONTAMINATE

EC50 - for Algae / Aquatic Plants 100 mg/l/72h

Chronic NOEC for Algae / Aquatic Plants 100 mg/l

12.2. Persistence and degradability

Hydrocarbons, C10-C13, n-alkanes,
isoalkanes, cyclics, < 2% aromatics
Rapidly degradable

(R)-P-MENTHA-1,8-DIENE

Solubility in water 0,1 - 100 mg/l

Rapidly degradable

2-BUTOXYETHANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

90%

Sulfuric acid, mono-C12-14-alkyl esters,
sodium salts

Rapidly degradable

Sodium thioglycolate

Rapidly degradable

12.3. Bioaccumulative potential

(R)-P-MENTHA-1,8-DIENE

Partition coefficient: n-octanol/water 4,38

BCF 1022

2-BUTOXYETHANOL

Partition coefficient: n-octanol/water 0,81

BCF 2,5

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available



40404 - 404045

Revision nr. 5

OXIDO IRON DECONTAMINATE

Dated 05/06/2023

Printed on 05/06/2023

Page n. 16/21

Replaced revision:4 (Dated: 05/06/2023)

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 3082

ADR / RID: In accordance with Special Provision 375, this product, when is packed in receptacles of a capacity \leq 5Kg or 5L, is not submitted to ADR provisions.

IMDG: In accordance with Section 2.10.2.7 of IMDG Code, this product, when is packed in receptacles of a capacity \leq 5Kg or 5L, is not submitted to IMDG Code provisions.

IATA: In accordance with SP A197, this product, when is packed in receptacles of a capacity \leq 5Kg or 5L, is not submitted to IATA dangerous goods regulations.

14.2. UN proper shipping name

ADR / RID: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (D-limonene)

IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (D-limonene)

IATA: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (D-limonene)

14.3. Transport hazard class(es)

ADR / RID: Class: 9 Label: 9



IMDG: Class: 9 Label: 9



IATA: Class: 9 Label: 9



14.4. Packing group

ADR / RID, IMDG, IATA: III



40404 - 404045

Revision nr. 5

Dated 05/06/2023

Printed on 05/06/2023

Page n. 17/21

Replaced revision:4 (Dated: 05/06/2023)

OXIDO IRON DECONTAMINATE

14.5. Environmental hazards

ADR / RID: Environmentally Hazardous



IMDG: Marine Pollutant



IATA: Environmentally Hazardous



14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 90	Limited Quantities: 5 L	Tunnel restriction code: (-)
	Special provision: 274, 335, 375, 601		
IMDG:	EMS: F-A, S-F	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 450 L	Packaging instructions: 964
	Pass.:	Maximum quantity: 450 L	Packaging instructions: 964
	Special provision:	A97, A158, A197, A215	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance



40404 - 404045

Revision nr. 5

Dated 05/06/2023

Printed on 05/06/2023

Page n. 18/21

Replaced revision:4 (Dated: 05/06/2023)

OXIDO IRON DECONTAMINATE

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Met. Corr. 1	Substance or mixture corrosive to metals, category 1
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4



40404 - 404045

Revision nr. 5

Dated 05/06/2023

Printed on 05/06/2023

Page n. 19/21

Replaced revision:4 (Dated: 05/06/2023)

OXIDO IRON DECONTAMINATE

Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
Skin Sens. 1B	Skin sensitization, category 1B
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H361f	Suspected of damaging fertility.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level



40404 - 404045

Revision nr. 5

Dated 05/06/2023

Printed on 05/06/2023

Page n. 20/21

Replaced revision:4 (Dated: 05/06/2023)

OXIDO IRON DECONTAMINATE

- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2019/521 (XII Atp. CLP)
 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
 17. Regulation (EU) 2019/1148
 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.



40404 - 404045

Revision nr. 5

Dated 05/06/2023

Printed on 05/06/2023

Page n. 21/21

Replaced revision:4 (Dated: 05/06/2023)

OXIDO IRON DECONTAMINATE

Changes to previous review:
The following sections were modified:
01.